

TYPICAL JOINT ON WATER
AND SEWER SERVICE PIPES
N.T.S.

KEY TO NUMBERED PARTS:

- (1) WATER SERVICE CARRIER PIPE 100mm DIA. HDPE IPS DR 13.5 (860 kPa) WITH 50mm NOMINAL POLYURETHANE INSULATION AND FACTORY INSTALLED JACKET.
- (13) POLYURETHANE HALF SHELL CUT TO LENGTH AND COATED WITH ASPHALT MASTIC.
- (40) FIELD COAT ALL POLYURETHANE WITH MASTIC.
- (41) BUTT FUSION JOINT TO BE MADE BY A QUALIFIED AND LICENSED TECHNICIAN.
- 42) SHOP CAST 50mm THICK POLYURETHANE INSULATION WITH WITH BLACK JACKET PROTECTIVE COATING.
- (43) HEAT SHRINK SLEEVE MIN. 100mm LAP ON BLACK JACKET AFTER SHRINKAGE.

RESOLUTE BAY

UTILIDOR REPAIRS RESOLUTE BAY NUNAVUT



A. D. Williams
Engineering Inc.
Consulting Engineers

#4903-47 Street P.O. Box 1529 Yellowknife, NT X1A 2P2 (867) 873-2395 (867) 873-2547

Edmonton Office (780) 424-2393 (780) 425-1520 ADWE NO.:

DESIGN BY:	DEC	DATE: 03.07.29	
	DFG	SCALE: N.T.S.	
DRAWN BY:	DFG	DWG NO:	REV NO:
	DFG	CI/7	A
APPROVED BY:	550		
	BFG		<i>D</i> N

D. WILLIAMS CADFILE: 7731