

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
	Not controlled		

Product Name	PRODURO TO-4+ XL SYNTHETIC BLEND	Code	PD4XLLT, 420-037-0	
	LO-TEMP (TDTO)			
Synonym	Not available	Validated o	n 5/21/2003.	
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency	Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre: Consult local telephone directory for	
Material Uses	An SAE 0W-20 grade multipurpose transmission, hydraulic, wet brake and final drive fluid intended for use where Caterpillar TO-4 quality oils are recommended.		emergency number(s).	

Section 2. Composition and Information on Ingredients						
				Ex	oosure Limits (ACGIH)	
	Name	CAS#	% (W/W)	TLV-TWA(8 h)	STEL	CEILING
Mixture of severely hydrotreated and hydrocracked base oil (petroleum), synthetic hydrocarbons and other proprietary, non-hazardous additives.		Mixture	100	5 mg/m³ (oil mist)	10 mg/m³ (oil mist)	Not established
Manufacturer Recommendation	Not applicable					
Other Exposure Limits	Consult local, state, provincial or territory authorities for acceptable exposure limits.					

Section 3. Hazards Identification.		
Potential Health Effects	Non irritating to slight transient irritation to skin and eyes, but no permanent damage. Relatively non-toxic via ingestion. This product has a low vapour pressure and is not expected to present an inhalation exposure at ambient conditions. Upon heating to high temperatures, or mechanical actions which may produce vapours or mists, inhalation of product may cause irritation of the breathing passages. For more information, refer to Section 11.	

Section 4. First	Section 4. First Aid Measures		
Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.		
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention.		
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.		
Ingestion	DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.		
Note to Physician	Not available		

Flammability	May be combustible at high temperature.	Flammable Limits	Not available
Flash Points	OPEN CUP: 209°C (408.2°F) (Cleveland)	Auto-Ignition Temperature	Not available
Fire Hazards in Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.
Products of Combustion	Carbon oxides (CO, CO2), nitrogen oxides (NOx incomplete combustion.), sulphur oxides (SC	x), smoke and irritating vapours as products of

Continued on Next Page Available in French

PRODURO TO-4" XL	SYNTHETIC BLEND LO-TEMP (TDTO)
Fire Fighting	NAERG96, GUIDE 171, Substa
Media and	for 800 meters (0.5 mile) in all

ances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals, foam, water spray or CO2. LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel.

Page Number: 2

Section 6. Accidental Release Measures

Material Release or Spill

nstructions

Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities

Section 7. Ha	Section 7. Handling and Storage		
Handling	Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid skin contact. Avoid eye contact. Avoid inhalation of product vapours or mists. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.		
Storage	Store in dry, cool, well-ventilated area. Keep container tightly closed. Store away from incompatible and reactive materials (See section 5 and 10).		

Section 8. Exposure Controls/Personal Protection

Engineering Controls For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station

Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use.

Eyes Eye protection (i.e., safety glasses, safety goggles and/or face shield) should be determined based on conditions of use. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered.

Body Wear appropriate clothing to prevent skin contact. As a minimum long sleeves and trousers should be worn.

Respiratory Where concentrations in air may exceed the occupational exposure limits given in Section 2 (and those applicable to your area) and where engineering, work practices or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.

Hands Wear appropriate chemically protective gloves. When handling hot product ensure gloves are heat resistant and insulated.

Feet Wear appropriate footwear to prevent product from coming in contact with feet and skin.

Section 9. Physical and Chemical Properties			
Physical State and Appearance	Viscous liquid.	Viscosity	35.1 cSt @ 40°C (104°F), 7.4 cSt @ 100°C (212°F), VI=184
Colour	Amber.	Pour Point	-51°C (-60°F)
Odour	Hydrocarbon.	Softening Point	Not applicable.
Odour Threshold	Not available	Dropping Point	Not applicable.
Boiling Point	Not available	Penetration	Not applicable.
Density	0.8519 kg/L @ 15°C (59°F).	Oil / Water Dist. Coefficient	Not available
Vapour Density	Not available	Ionicity (in water)	Not available
Vapour Pressure	Negligible at ambient temperature and pressure.	Dispersion Properties	Not available
Volatility	Non-volatile.	Solubility	Insoluble in water.

Continued on Next Page Available in French

Section 10. Stability and Reactivity			
Corrosivity	Copper corrosion, 3h, 100°C (ASTM D0130): 1	a	
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances / Conditions to Avoid	Reactive with oxidizing agents and acids.	Decomposition Products	May release COx, SOx, H2S, POx, ZnOx, CaOx, aldehydes, alkyl mercaptans, sulfides, methacrylate monomers, smoke and irritating vapours when heated to decomposition.

Section 11. Toxicological In	formation
Routes of Entry	Skin contact, eye contact, inhalation and ingestion.
Acute Lethality	Based on toxicity of components. Acute oral toxicity (LD50): >5000 mg/kg (rat). Acute dermal toxicity (LD50): >2000 mg/kg (rabbit). Acute inhalation toxicity (LC50): >2500 mg/m³/4h (rat).
Chronic or Other Toxic Effects Dermal Route:	Prolonged or repeated contact may cause skin irritation characterized by dermatitis or oil acne.
Inhalation Route:	Negligible breathing hazard at normal temperatures (up to 38°C) or recommended blending temperatures. Elevated temperatures or mechanical action may form vapours, mists or fumes. Inhalation of oil mists or vapours from hot oil may cause irritation of the upper respiratory tract.
Oral Route:	Low toxicity; has laxative effect.
Eye Irritation/Inflammation:	Repeated or prolonged contact may cause transient irritation, but no permanent damage.
Immunotoxicity:	Not available
Skin Sensitization:	This product is not expected to be a skin sensitizer, based on the available data and the known hazards of the components.
Respiratory Tract Sensitization:	This product is not expected to be a respiratory tract sensitizer, based on the available data and the known hazards of the components.
Mutagenic:	Based on actual test results of base oils and results of similar products, severely hydrotreated base oils give negative results when tested for: (a) Salmonella Typhimurium TA98 using the Modified Ames Assay for Petroleum Product; (b) Salmonella-Escherichia coli/Mammalian-Microsome Reverse Mutation Assay (Ames test) with a Confirmatory Assay; (c) Structural Chromosomal Aberrations in Chinese Hamster Ovary (CHO) Cells.
Reproductive Toxicity:	This product is not expected to be a reproductive hazard, based on the available data and the known hazards of the components.
Teratogenicity/Embryotoxicity:	This product is not expected to be a teratogen or an embryotoxin, based on the available data and the known hazards of the components.
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at reportable quantities that are listed as A1 or A2 carcinogens by ACGIH.
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as group 1, 2A or 2B carcinogens by IARC.
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by IRIS.
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.
Other Considerations	No additional remark.

Section 12. Ecolo	gical Information	
Environmental Fate	Not available	Persistance/ Not available Bioaccumulation Potential
BOD5 and COD	Not available	Products of Not available Biodegradation
Additional Remarks	No additional remark.	

Continued on Next Page Available in French

Section 13. Disposal Considerations

Waste Disposal

Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal

Section 14. Transport Information					
TDG Classification	Not controlled under TDG (Canada).	Special Provisions for Transport	Not applicable.		

Section 15. Regu	latory Information					
Other Regulations	This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation a the CEPA-DSL (Domestic Substances List).					
	All components of this formulation are listed on the US EPA-TSCA Inventory.					
	All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).					
	This product has been classified in accordance the MSDS contains all of the information requi	be with the hazard criteria of the Controlled Products Regulations (CPR) and red by the CPR.				
	Please contact Product Safety for more inform	ation.				
DSD/DPD (Europe)	Not classified under the Dangerous Substances or Dangerous Preparations Directives.	HCS (U.S.A.) Not controlled under the HCS (United States).				
ADR (Europe) (Pictograms)	NOT EVALUATED FOR EUROPEAN TRANSPORT NON ÉVALUÉ POUR LE TRANSPORT EUROPÉEN.	DOT (U.S.A) (Pictograms)				
HMIS (U.S.A.)	Health Hazard Tire Hazard Reactivity 1 NFPA (U	Health 1 0 Reactivity 1 Slight 2 Moderate				
	Personal Protection B	Specific hazard 3 High 4 Extreme				

Section 16. Other Information

References

Available upon request.

* Margue de commerce de Petro-Canada - Trademark

Glossarv

ACGIH - American Conference of Governmental Industrial Hygienists

ADR - Agreement on Dangerous goods by Road (Europe) ASTM - American Society for Testing and Materials (

BOD5 - Biological Oxygen Demand in 5 days

CAN/CGA B149.2 Propane Installation Code

CAS - Chemical Abstract Services

CEPA - Canadian Environmental Protection Act

CERCLA - Comprehensive Environmental Response, Compensation and Liability

Act

CFR - Code of Federal Regulations

CHIP - Chemicals Hazard Information and Packaging Approved Supply List

COD5 - Chemical Oxygen Demand in 5 days CPR - Controlled Products Regulations

DOT - Department of Transport

DSCL - Dangerous Substances Classification and Labeling (Europe)

DSD/DPD - Dangerous Substances or Dangerous Preparations Directives

(Europe)

DSL - Domestic Substance List

EEC/EU - European Economic Community/European Union

EINECS - European Inventory of Existing Commercial Chemical Substances

EPCRA - Emergency Planning and Community Right to Know Act

FDA - Food and Drug Administration

FIFRA - Federal Insecticide, Fungicide and Rodenticide Act

HCS - Hazardous Communication System

HMIS - Hazardous Material Information System

IARC - International Agency for Research on Cancer

IRIS - Integrated Risk Information System

LD50/LC50 - Lethal Dose/Concentration kill 50%

LDLo/LCLo - Lowest Published Lethal Dose/Concentration

NAERG'96 - North American Emergency Response Guide Book (1996)

NFPA - National Fire Prevention Association

NIOSH - National Institute for Occupational Safety & Health

NPRI - National Pollutant Release Inventory

NSNR - New Substances Notification Regulations (Canada)

NTP - National Toxicology Program

OSHA - Occupational Safety & Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

SARA - Superfund Amendments and Reorganization Act

SD - Single Dose

STEL - Short Term Exposure Limit (15 minutes)

TDG - Transportation Dangerous Goods (Canada)

TDLo/TCLo - Lowest Published Toxic Dose/Concentration

TLm - Median Tolerance Limit

TLV-TWA - Threshold Limit Value-Time Weighted Average

TSCA - Toxic Substances Control Act

USEPA - United States Environmental Protection Agency

USP - United States Pharmacopoeia

WHMIS - Workplace Hazardous Material Information System

For Copy of MSDS

Prepared by Product Safety - JDW on 5/21/2003.

Continued on Next Page Available in French

PRODURO TO-4" XL SYNTHETIC BLEND LO-TEMP (TDT	n
---	---

Page Number: 5

The Canadian Controlled Products Regulations (CPR) (Under the Hazardous Products Act, part of the WHMIS legislation) only apply to WHMIS Controlled (i.e., hazardous) products. Therefore, the CPR and the 3-year update rule specified therein do not apply to WHMIS Non-Controlled products. Although this is true, customarily Petro-Canada reviews and updates Non-Controlled product MSDS if a customer requests such an update. These Non-Controlled product updates are given a lower priority than Controlled products but are handled as soon as practicable. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:

Data entry by Product Safety - JDW.

Internet: www.petro-canada.ca

Lubricants:

Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564

Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax:

1-800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 800-201-6285

For Product Safety Information: (905) 804-4752

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.