



WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
\mathbf{G}	D-2A, D-2B		

Section 1. Cl	hemical Product and Company Identification		
Product Name	PETRO-CANADA ANTIFREEZE	Code	W269
Synonym	Universal Antifreeze, Radiator Antifreeze, Diesel Antifreeze, Petro-Canada Antifreeze-Coolant, Petro-Canada Heavy Duty Antifreeze-Coolant, Pre-Mix Antifreeze, Petro-Canada Premium Radiator Antifreeze, Diesel Engine Coolant, Pre-Mixed Radiator Antifreeze/Coolant Petro-Canada.		on 5/11/2005.
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency	Petro-Canada: 403-296- 23000 Canutec Transportation: 613-996-6666 Poison Control Centre:
Material Uses	Used as an engine antifreeze coolant.		Consult local telephone directory for emergency number(s).

	•			Ехро	osure Limits (ACGII	1)
	Name	CAS#	% (W/W)	TLV-TWA(8 h)	STEL	CEILING
Ethylene glycol		107-21-1	<u>></u> 45	Not established	Not established	100 mg/m³ (aerosol)
Sodium tetraborate pentahydrate (Diesel Engine Coolant only)		12179-04-3	<u><</u> 5	1 mg/m³	Not established	Not established
Manufacturer Recommendation	Not applicable					
Other Exposure Limits	Consult local, state, provincia	al or territory au	thorities for a	acceptable exposure	limits.	

Section 3. Hazards Identification.		
Potential Health Effects	Contact with this product may cause eye irritation. Not expected to cause more than slight skin irritation. Inhalation of this product may cause respiratory tract irritation. Ingestion may be extremely hazardous. May cause teratogenicity/embryotoxicity. May cause damage to reproductive organs. For more information refer to Section 11 of this MSDS.	

Section 4. First	Aid Measures
Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention.
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.
Ingestion	DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.
Note to Physician	Not available

Section 5. Fire	e-fighting Measures		
Flammability	May be combustible at high temperature.	Flammable Limits	Lower: 3.2%, Upper: 15.3%
Flash Points	Closed Cup: 116°C (241°F) (Tagliabue) Open Cup: 116°C (241°F) (Cleveland)	Auto-Ignition Temperature	413°C (775°F)
Fire Hazards in Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container.
Continued on Next	Page Internet: www.petro-ca	anada ca/msds	Available in French

Continued on Next Page Internet: www.petro-canada.ca/msds Available in French

PETRO-CANADA A	NTIFREEZE	Page Number: 2
Products of Combustion	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incom	plete combustion.
Fire Fighting Media and Instructions	NAERG2004, GUIDE 171, Substances (low to moderate hazard). If tank, rai fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initia mile) in all directions. Shut off fuel to fire if it is possible to do so without withdraw from area and let fire burn out under controlled conditions. Withdraw from venting safety device or any discolouration of tank due to fire. C spray in order to prevent pressure build-up, autoignition or explosion. SM foam, water spray or CO2. LARGE FIRE: use water spray, fog or foam. For extinguishers may be used, and self contained breathing apparatus (SCB indoor fires and any significant outdoor fires, SCBA is required. Respiratory for fire fighting personnel.	Il evacuation for 800 meters (0.5 at hazard. If this is impossible, raw immediately in case of rising collocontaining vessels with water ALL FIRE: use DRY chemicals, small outdoor fires, portable fire A) may not be required. For all

Section 6. Accidental Release Measures

Material Release or Spill

IN THE EVENT OF A LARGE SPILL CONSIDER THE FOLLOWING CONTROL MEASURES: Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Ventilate area. Ensure clean-up personnel wear appropriate personal protective equipment. Avoid breathing vapours or mists of material. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately.

Section 7.	Section 7. Handling and Storage				
Handling	Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid confined spaces and areas with poor ventilation. Avoid skin contact. Avoid eye contact. Avoid inhalation of product vapours or mists. Do not ingest this product. Wear proper personal protective equipment (See Section 8). Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.				
Storage	Store in dry, cool, well-ventilated area. Store away from heat and sources of ignition. Keep container tightly closed. Store away from incompatible and reactive materials (See section 5 and 10).				

Section 8. Exposure Controls/Personal Protection

Engineering Controls

For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.

Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use.

Eyes Chemical splash goggles should be worn when handling this material.

Body If this material may come into contact with the body during handling and use, we recommend wearing appropriate protective clothing to prevent contact with the skin. (Contact your PPE provider for more information)

Respiratory A minimum of NIOSH-approved air-purifying respirator with a organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

Hands If this material may come in contact with the hands during handling and use, we recommend wearing gloves of the following material(s): Neoprene, Polyvinyl chloride (PVC). Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns.

Feet Wear appropriate footwear to prevent product from coming in contact with feet and skin.

Section 9. Physical and Chemical Properties				
Physical State and Appearance	Clear viscous liquid.	Viscosity	Not available	
Colour	Green.	Pour Point	Not available	
Odour	Odourless.	Softening Point	Not applicable.	
Odour Threshold	Not available	Dropping Point	Not applicable.	
Boiling Point	129 to 197°C (264 to 387°F)	Penetration	Not applicable.	
Density	1.07 to 1.145 (Water = 1)	Oil / Water Dist. Coefficient	Not available	
Continued on Next P	lage Internet: v	vww.petro-canada.ca/msds		Available in French

PETRO-CANADA ANTIFREEZE			Page Number: 3
Vapour Density	2.1 (Air=1).	Ionicity (in water)	Not available
Vapour Pressure	0.06 mmHg @ 20°C (68°F).	Dispersion Properties	Not available
Volatility	0% (w/w)	Solubility	Soluble in water, methanol and diethyl ether.

Section 10. Sta	Section 10. Stability and Reactivity			
Corrosivity	Not available			
Stability	The product is stable.	Hazardous Polymerization	Will not occur under normal working conditions.	
Incompatible Substances / Conditions to Avoid	Reactive with oxidizing agents, acids, alkalis, perchloric acid, phosphorus and silvered copper wires carrying DC current.	Decomposition Products	May release COx, acrid smoke and irritating vapours when heated to decomposition.	

Section 11. Toxicological Information			
Routes of Entry	Skin contact, eye contact, inhalation and ingestion.		
Acute Lethality	Ethylene glycol (107-21-1): LD50: 4700 mg/kg (oral/rat). LD50: 9530 mg/kg (dermal/rabbit). Sodium tetraborate pentahydrate (12179-04-3):		
Ohanania an Othan Tarria Effa	LD50: 3200-3500 mg/kg (oral/rat) (Boric acid). [Sodium tetraborate pentahydrate]		
Chronic or Other Toxic Effer Dermal Route:	Short-term exposure is expected to cause only slight irritation, if any.		
Inhalation Route:	Inhalation of this product may cause respiratory tract irritation.		
Oral Route:	Extremely dangerous in case of ingestion.		
Eye Irritation/Inflammation:	This product contains a component (at >= 1%) that can cause eye irritation. Therefore, this product is considered to be an eye irritant.		
Immunotoxicity:	Not available		
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components.		
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components.		
Mutagenic:	This product is not known to contain any components at \geq 0.1% that have been shown to cause mutagenicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a mutagen.		
Reproductive Toxicity:	Borates are possible reproductive toxins based upon available animal ingestion studies in several species. These studies usually involved high doses, over prolonged periods of time. A human study following occupational exposure to borate by inhalation concluded that, no adverse effects to reproduction were found in this population, under the conditions of this study.		
Teratogenicity/Embryotoxicity:	This product contains a component(s) at $>= 0.1\%$ that has been shown to cause teratogenicity and/or embryotoxicity in laboratory tests. Therefore, this product is considered to be a teratogen/embryotoxin (Ethylene glycol).		
Carcinogenicity (ACGIH):	ACGIH A4: not classifiable as a human carcinogen (Ethylene glycol). This product is not known to contain any chemicals at reportable quantities that are listed as Group A1, A2, or A3 carcinogens by ACGIH.		
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as Group 1, 2A, or 2B carcinogens by IARC.		
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.		
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by IRIS.		
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.		
Other Considerations	The substance may be toxic to kidneys and liver. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.		

PETRO-CANADA AN	ITIFREEZE		Page Number: 4	
Section 12. Ecological Information				
Environmental Fate	Not available	Persistance/ Bioaccumulation Potential	Not available	
BOD5 and COD	Not available	Products of Biodegradation	Not available	
Additional	No additional remark.			

Section 13. Disposal Considerations

Remarks

Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional Waste Disposal authorities. Ensure that waste management processes are in compliance with government requirements and

local disposal regulations.

Section 14. Transport Information					
TDG Classification Not a hazardous material for transport according to the TDG Regulations. (Canada)	Special Provisions for Transport	Not applicable.			

Section 15. Regulatory Information Other All of the components of this product are on the Domestic Substances List (DSL), are considered to be on the DSL, or are exempt from the New Substance Notification (NSN) requirements. Regulations All components of this formulation are listed on the US EPA-TSCA Inventory. This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. Please contact Product Safety for more information. **DSD/DPD (Europe)** Not evaluated. HCS (U.S.A.) CLASS: Target organ effects. CLASS: Irritating substance. NOT EVALUATED FOR DOT (U.S.A) ADR (Europe) **EUROPEAN TRANSPORT** (Pictograms) (Pictograms) NON ÉVALUÉ POUR LE HMIS (U.S.A.) **Health Hazard** 2* NFPA (U.S.A.) Rating 0 Insignificant Fire Hazard 1 Slight Fire Hazard 1 Health 0 Reactivity 2 Moderate 0 Reactivity 3 High Specific hazard Personal Protection 4 Extreme

Section 16. Other Information

Available upon request. References

* Marque de commerce de Petro-Canada - Trademark

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists

ADR - Agreement on Dangerous goods by Road (Europe)

ASTM - American Society for Testing and Materials BOD5 - Biological Oxygen Demand in 5 days

CAN/CGA B149.2 Propane Installation Code

CAS - Chemical Abstract Services

CEPA - Canadian Environmental Protection Act

CERCLA - Comprehensive Environmental Response, Compensation

and Liability Act

CFR - Code of Federal Regulations

CHIP - Chemicals Hazard Information and Packaging Approved Supply

CNS - Central Nervous System

COD5 - Chemical Oxygen Demand in 5 days

CPR - Controlled Products Regulations

DOT - Department of Transport

DSCL - Dangerous Substances Classification and Labeling (Europe)

DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe)

DSL - Domestic Substance List

EEC/EU - European Economic Community/European Union

EINECS - European Inventory of Existing Commercial Chemical Substances

Continued on Next Page

USP - United States Pharmacopoeia

Available in French Internet: www.petro-canada.ca/msds

IRIS - Integrated Risk Information System

LD50/LC50 - Lethal Dose/Concentration kill 50%

LDLo/LCLo - Lowest Published Lethal Dose/Concentration

NAERG'96 - North American Emergency Response Guide Book (1996)

NFPA - National Fire Prevention Association

NIOSH - National Institute for Occupational Safety & Health

NPRI - National Pollutant Release Inventory

NSNR - New Substances Notification Regulations (Canada)

NTP - National Toxicology Program

OSHA - Occupational Safety & Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTECS - Registry of Toxic Effects of Chemical Substances SARA - Superfund Amendments and Reorganization Act

SD - Single Dose

STEL - Short Term Exposure Limit (15 minutes)

TDG - Transportation Dangerous Goods (Canada)

TDLo/TCLo - Lowest Published Toxic Dose/Concentration TLm - Median Tolerance Limit

TLV-TWA - Threshold Limit Value-Time Weighted Average

TSCA - Toxic Substances Control Act

USEPA - United States Environmental Protection Agency

PETRO-CANADA ANTIFREEZE Page Number: 5 EPA - Environmental Protection Agency WHMIS - Workplace Hazardous Material Information System EPCRA - Emergency Planning and Community Right to Know Act FDA - Food and Drug Administration FIFRA - Federal Insecticide, Fungicide and Rodenticide Act HCS - Hazard Communication Standard HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer Prepared by Product Safety - JDW on 5/11/2005. For Copy of MSDS Internet: www.petro-canada.ca/msds Data entry by Product Safety - RS. Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228 For Product Safety Information: (905) 804-4752

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.