<u> 330</u>

FERGUSON SIMEK CLARK

ENGINEERS AND ARCHITECTS

Our File: 95 1191

October 20, 1997

Paul Smith Water Resources Officer DIAND Nunavut District Box 100 Igaluit, NT XOA 0H0 RECEIVED

OCT 23 1997.

D.I.A.N.D.

NS L3-16-63

DECEIVEN OCI 8 / 1997

Re: Cape Dorset Sewage and Solid Waste

Your Information Request of September 17, 1997

As you requested, please find a copy of the Design and Operational Concepts Brief provided by FSC to the Hamlet of Cape Dorset in June of 1996.

I would like to provide you with some background information regarding the development of that brief and our subsequent discussions with the community.

When we arrived, the lagoon and solid waste site had already been chosen by the community and work had begun. The brief we provided outlined an annual retention lagoon based on the 10 year population, and a solid waste site operated with a trench method.

Since that brief we determined that the site was, in fact, too steep and too small in area to accommodate an annual retention lagoon. We were also concerned about the quality of the granular materials that may be used in the construction.

Instead, we suggested to the community a short detention sewage dumping site followed by overland flow (wetland) treatment. FSC also suggested that the land below the dumping site should be graded to maximize liquid coverage and minimize the potential for erosion. This type of system is being used successfully in several Keewatin communities, and is sanctioned by the Water Board.

Finally, following the construction of test pits during the summer of 1996, we determined that a trench method may not be an appropriate operating strategy and that an area method may be more appropriate.

These recommendations were provided to the community during visits in September 1996 shown in the sketch included with the brief. Earlier in August 1996, FSC was invited to propose services for the relocation of the sewage lagoon and solid waste site; however, we were not awarded the job. Since that time, FSC has not been in the community to see what has been implemented. A telephone conversation with Jim Strickland in the early winter of 1996 determined that Cape Dorset was pleased with our earlier recommendations that some work had been undertaken, but details were limited.

YEŁLOWKNIFE 4910 53 Street, P.O.Box 1777, Yellowknife, NT Canada X1A 2P4 Tel: (403) 920-2882, Fax: (403) 920-4319, email: fscyk@fsc.ca

[•] IQALUIT building 1052, P.O.Box 1779, Iqaluit, NT Canada X0A 0H0 Tel: (819) 979-0555, Fax: (819) 979-5711, email: fsc@nunanet.com

INUVIK 1 - 3 Council Crescent, P.O.Box 2385, Inuvik, NT Canada X0E 0T0 Tel: (403) 979-2427, Fax: (403) 979-3025, email: fscinuvk@permafrost.com

We will contact the Hamlet directly to discuss the present situation and offer to assist them in the establishment of an acceptable waste disposal infrastructure.


I hope the brief and this letter provides you with the information you seek. Please contact me if you have questions.


Yours truly, FERGUSON SIMEK CLARK


Kevin Hodgins, P. Eng.


Principal.

cc Timoon Toonoo, SAO Hamlet of Cape Dorset fax 819 897-8030 Terry Gray, FSC Iqaluit









- EXISTING GROUND GRANLAR BERM --

BERM CONSTRUCTION

- Berms to be constructed of acceptable granular fill.
- Borrow source to be determined by the engineer.

DISPOSAL PROCESS

- Maste to be dumped from the truck directly into the sewage

retaining logoon Effluent to be discharged arrivally in the fall through the well-vegetated drainage course to the ocean.

SEMAGE LAGOON Ę



SOVER.

EXISTING GROUND

CELL CONSTRUCTION

Berms to be constructed of acceptable granular IIII Berm dimensions to be 2 metres in height with a 2 metres top width backslopes not to be steeper than 3.1

impermeable liner to be placed within berm and keyed to top Granular protective cover to be provided over liner

DISPOSAL PROCESS

Maste oil currently stored within sealed containers to be collected and relocated
to the new retention cell for disposal.
 Maste oil to be stored within sealed containers and disposed of within the retention cell.

MASTE OIL RETENTION CELL Š

GRANJLAR PAD SLOPE FOR



FERGIBON BACK CLARK PARTY CANADA JAN BY

GROUP

PAD CONSTRUCTION

- Pad to be constructed of acceptable granular fill - Pad dimensions to be 300 mm in height backslopes not to be steeper than 3:1 top to be graded for drainage at 1% (minimum)

DISPOSAL PROCESS

Maske to be disposed of on the pad in a neat and orderly manner Existing Bulky Moste to be relocated and disposed of at the new bulky waste disposal pad.

BULK WASTE DISPOSAL PAD

EXISTING GROUND TO BE EXCAVATED TO PROVIDE POSITIVE DRAINAGE

EXISTING GROUND 000 MIN

DRAINAGE DITCH SECTION (TYP.

BEWACE LAGOON CAPE DORBEI FELOCATION

CAPE DORBET, NT LAGOON DETAILS

NIS	JUNE 20, 1996	CALLEY PROGET IN	715.48 to. 95-1190	On Deserta	H 5
K,H,	J.P.W.	K.H.	75C TE HE CESSE, DAYG	1234	در و در

記