


- FLOOR DRAINS TO TYPE SPECIFIED INSTALLED IN VOID SPACE OF FLOOR. HOLE DRILLED IN JOISTS TO BE REINFORCED. CO-ORDINATE WITH JOIST LOCATIONS.
- 2 PROVIDE CLEAN OUTS FOR DRAINS
- POLYETHYLENE SUMP PIT TO BE RECESSED INTO FLOOR C/W SUMP PUMP.
  SUMP TO BE INSTALLED THROUGH FLOOR. TOP OF SUMP TO BE LEVEL WITH
- 50mm FILTER DRAIN TO CONNECT TO SUMP UNDER FLOOR.
- 5 ELECTRIC HOT WATER TANK MOUNTED UNDER COUNTER.
- 19mmØ DOMESTIC COLD WATER LINE CONNECT TO SINK FIXTURE AND HOT WATER TANK. VERIFY LOCATION ON SITE. EXTEND 13mmØ WATER CONNECTION TO EACH FIXTURE. PROVIDE SHUT-OFF VALVES ON BOTH WATER CONNECTIONS.
- 7 WATER STORAGE TANK
- 8 50mm PVC PIPING BETWEEN SUMP AND WASTE WATER TANK.
- 9 WASTEWATER TANK TO BE MOUNTED ON SLEEPER 50mm ABOVE FLOOR OF FACILITY.
- 10 ALL PLUMBING VENTS TO BE INSTALLED AT HIGH LEVEL AND PENETRATE ROOF.

ORIGINAL SIGNED
BY ENGINEER

75mmØ PUMPED SANITARY DISCHARGE PIPE.



2 WASTE WATER SUMP DETAIL
306 306 SCALE 1:10


## Conditions of Use

Verify elevations and/or dimensions on drawing prior to use. Report any discrepancies to Dillon Consulting Limited.

Do not scale dimensions from drawing.

Do not modify drawing, re-use it, or use it for purposes other than those intended at the time of its preparation without prior written permission from Dillon Consulting Limited.







<b>ON</b> TING

					DESIGN	REVIEWED BY	i
					WCDD	GS	ĺ
<b>)</b>					DRAWN	CHECKED BY	Ĺ
					AJP	GS	ſ
					7 (6)		
					DATE		ĺ
	3	ISSUED FOR TENDER	06/06/08	GS	JUNE 2008		
	2	ISSUED FOR 100% CLIENT REVIEW	04/30/08	GS			ĺ
	1	ISSUED FOR CLIENT REVIEW	03/15/08	GS		DR: 1:500	
	No.	ISSUED FOR	DATE	BY	VE	:RT: 1:50	ĺ

	SHEET NO.
DOMESTIC PLUMBING	306

07-8107-2000

TALOYOAK WATER TREATMENT PLANT

TALOYOAK, NUNAVUT