



*An ATCO Frontec and Pan Arctic Inuit Company*

Serial No. 2094-CNC

30 September 2008

Manager of Licensing  
Nunavut Water Board  
P.O. Box 119  
Gjoa Haven, Nunavut  
X0B 1J0

**Attention:** Ms. Phyllis Beaulieu

**Subject:** Application for New Water Licence – Dewar Lakes

**References:** A. Licence NWB6FOD0409 – Type “B”, Dewar Lakes (“FOX-3”),  
Nunavut;  
B. Letter from NWB dated 26 August 2008.

---

Dear Ms. Beaulieu:

Please find attached the following items in support of Nasittuq’s application for a new Water Licence for Dewar Lakes (“FOX-3”):

- completed Water Licence Application Form for Dewar Lakes (“FOX-3”) (Attachment 1);
- completed Exploration/Remote Camp Supplementary Questionnaire (Attachment 2);
- Inuktitut and English Summary of Project (Attachment 3);
- cheque for the Application Fee of \$30.00 (Attachment 4); and
- cheque for the Water Use Fee of \$30.00 (Attachment 5).

Currently there is a licence in place for the FOX-3 site under the Department of National Defence’s (“DND”) name (Reference “A”) which expires on 28 February 2009. The application for the licence was prepared by Nasittuq; however, in error, we submitted the application with DND as the Licensee instead of Nasittuq. This current application is submitted to correct this oversight, as recommended by the Nunavut Water Board (“NWB”) in the Reference “B” letter.

The following highlights some areas of particular interest for this application, which we feel are appropriate for this new licence, or which we have noted while administering the current licence:

**1. Sewage Handling System and Effluent Sampling Point FOD-2**

Sewage (blackwater) and greywater are combined in the sewage system. The sewage system comprises a sump, holding tank, and masticating pump within the building train, and a sewage outfall pipe leading to an outfall area on the land. This system has been in place since 1957. In 1995, the site changed from manned to unmanned status. Since then the site is visited by FOX-M staff on scheduled quarterly preventive and corrective maintenance trips and on an as needed basis. Little sewage is generated during these visits. During the months of May to September the site may be returned to manned status (ramped up) to support project activity. The amount of sewage depends on the number of people on-site.

Sewage is not discharged daily. When the sewage tank nears or reaches capacity, the sewage is discharged out the sewage outfall pipe to the designated outfall area. Up to 10 m<sup>3</sup> is discharged at one time from two to five times a year, depending on the number of people that have visited the site.

The site has one incinerating toilet which reduces sewage to ash; the ash is disposed of in the approved landfill. The incinerating toilet's cycling time (interval between usage) does not make it practical to support anything but a short site visit by a few staff. It is primarily in place in case the site fails in the winter and freezes. Under these conditions, a small crew would be dispatched to the site to restore power and thaw the site. The incinerating toilet would be used until the sewage system was thawed and returned to a serviceable state. It cannot meet the demands of a ramped up site.

We request the sewage effluent sampling be done during the month when the site is ramped up when there is active discharge, or a minimum once annually during those years when there is no ramp-up. The sampling point is FOD-2, the end of the sewage outfall pipe, as shown in the attached site plan (Annex B to the Exploration/Remote Camp Supplementary Questionnaire).

Sewage effluent samples will be analyzed for:

- a) Biochemical Oxygen Demand (BOD), total suspended solids (TSS), fecal coliforms, pH, phenols, and oil & grease;
- b) total arsenic, total copper, total iron, total mercury, total zinc, sulphate, total cadmium, total chromium, total lead, and total nickel; and
- c) nitrate-nitrite, sodium, magnesium, conductivity, ammonia nitrogen, potassium, and calcium.

## **2. Raw Water Intake and Monitoring Point FOD-1**

Water use varies depending on the number of people on-site from 0 m<sup>3</sup>/day (unmanned status) to a maximum of 2.9 m<sup>3</sup>/day (height of seasonal activity, ramped up site at full capacity). The seasonal activity from May to September varies from year to year; one season may have no projects, while the next season's projects may have the site at full capacity.

Please note that water is not drawn from the water lake daily. The site has four 10 m<sup>3</sup> (10,000 liter) raw water tanks. When the water in the tanks reaches a low level, an alarm alerts Nasittuq staff to fill the tanks with water from the water lake.

In order to fill up the four water tanks in one day and in order to meet the peak seasonal demand of a ramped up site, potentially at full capacity, Nasittuq requests a licence that allows the drawing of 40 m<sup>3</sup>/day (40,000 liters/day) up to three times in a month. This totals 120 m<sup>3</sup> (120,000 liters) in a 31-day month. This is less than half of the water usage currently allowed (310 m<sup>3</sup> in a 31-day month, drawn at 10 m<sup>3</sup>/day) by the site's Licence NWB6FOD0409 – Type "B". Please note that the filling of the water tanks up to three times in a month is only a potential seasonal occurrence if the site is at full capacity. When the site is unmanned, and only quarterly preventive/corrective maintenance visits occur, the water usage is greatly reduced and the raw water tanks may be filled up to three times during the entire period between October and April.

Nasittuq requests a licence that requires the recording of the daily quantity of raw water drawn from the water lake. We wish to confirm that the monitoring point for the water intake, FOD-1, is the flow meter installed inside the building train in the fill line to the raw water tanks and is not at the intake at the water lake itself. The flow meter was installed at this location for ease of reading and maintenance. We trust this is acceptable.

## **3. Emergency Response and Spill Reporting**

Nasittuq requests the NWB issues the new licence requiring spill reports based on the minimum reportable quantities of Schedule B of the Spill Contingency Planning and Spill Reporting Regulations as shown on the web site of the Nunavut Department of the Environment. The existing licence calls for the reporting of all spills. Nasittuq's current policy is to have our site staff report all spills internally, regardless of volume, as shown in Nasittuq's Spill Contingency Plan (Annex D to the Exploration/Remote Camp Supplementary Questionnaire).

Our Engineering Department uses this information to determine if there are any deficiencies in the Petroleum, Oil & Lubricants (POL) system, e.g. pressure relief valves required or not working, flex hoses which may be weeping indicating they require replacement, etc. As a result, we have spill reports for as little as 0.1 liter. Upon further review of the Spill Contingency Planning and Spill Reporting Regulations, Nasittuq notes that spills are to be reported as per Schedule B. As an example, the reportable limit for flammable liquids is 100 liters. By following the minimum reportable quantities of Schedule B, Nasittuq will be in compliance to the standards set by the Nunavut Department of the Environment.

Nasittuq has noted as per Section 76 of the Act, when applying for a new water licence, "The Board **may** require an applicant, a licensee or a prospective assignee to furnish and maintain security with the Minister in the form, of the nature, subject to such terms and conditions and in an amount prescribed by, or determined in accordance with, the regulations or that is satisfactory to the Minister." Nasittuq is the Agent under Contract to Public Works and Government Services Canada ("PWGSC") for the Operation and Maintenance of the North Warning System ("NWS"). This work is performed on DND property for which Nasittuq has care and custody for the duration of the Contract. Nasittuq understands that the NWS will continue to operate at least until 2030. Full ownership and responsibility for final disposition/reclamation of these NWS sites remains with the Department of National Defence.

Nasittuq believes that the North Warning System Contract itself provides the security required by the Board. Specifically, the North Warning System Contract provides security in the form of definitions of liability and subsequent insurance requirements for the Contractor ("Nasittuq") and also provides for Guarantors in the event of "Default of Contract" by the Contractor.

The NWS Contract is very specific in terms of Nasittuq's legal requirements and limitations of liability related to Government Property. Nasittuq is required to maintain insurance policies to cover liabilities for each occurrence (not less than) as follows:


- a) One Hundred Million Dollars (\$100,000,000) (Environmental ) for losses, injuries, damages, expenses, charges and Costs resulting from environmental damages; and
- b) Sixty Million Dollars (\$60,000,000) (Property) for loss or damages of Government Property.

The Cover Notes are provided to PWGSC on an annual basis for their review and approval. Nasittuq would be pleased to provide them to the Board upon request. Nasittuq believes that such insurance provides the necessary security guarantee required by the Minister in granting the licences.

In the interest of expediting this process, we would like to meet with you in your offices to review this application, to answer any questions you may have at that time, and also

clarify any term or condition of the Licence to ensure its effective administration. We will be contacting you shortly to arrange this meeting. In the meantime, if you have any questions or comments, you can contact Mr. Scott Charland, Senior Manager, Planning & Design at (613) 787-9626, or by email at [scott.charland@nasittuq.com](mailto:scott.charland@nasittuq.com).

Yours sincerely,  
**NASITTUQ CORPORATION**



Jacques Plante,  
President

cc: Sr. Manager, Planning and Design, Sr. Manager, Contracts and Supply Chain, Sr. Manager, Maintenance, CFO and Contracts

Attachments:

1. Water Licence Application Form for Dewar Lakes ("FOX-3")
2. Exploration/Remote Camp Supplementary Questionnaire
3. Inuktitut and English Summary of Project
4. Cheque for the Application Fee, payable to the Receiver General for Canada, in the amount of \$30.00
5. Cheque for the Water Use Fee, payable to the Receiver General for Canada, in the amount of \$30.00.



P.O. Box 119  
GJOA HAVEN, NU X0B 1J0  
TEL: (867) 360-6338  
FAX: (867) 360-6369

ᓇᓱᑦ ሀᓂᓱᑦ ንᓪᓗᓘᓘ  
NUNAVUT IMALIRIYIN KATIMAYINGI  
NUNAVUT WATER BOARD  
OFFICE DES EAUX DU NUNAVUT

## WATER LICENCE APPLICATION FORM

Application for: (check one)

New       Renewal       Amendment       Assignment       Cancellation

### LICENCE NO:

(for NWB use only)

#### 1. NAME AND MAILING ADDRESS OF APPLICANT/LICENSEE

Nasittuq Corporation  
Suite 100, 170 Laurier Avenue West  
Ottawa, Ontario, K1P 5V5  
Attention: Mr. Jacques Plante,  
President, Nasittuq Corporation and  
Project Director, North Warning System Project

Phone: (613) 234-9033 ext.833

Fax: (613) 234-2671

e-mail: jacques.plante@nasittuq.com

#### 2. ADDRESS OF CORPORATE OFFICE IN CANADA (if applicable)

Same

Phone: \_\_\_\_\_

Fax: \_\_\_\_\_

e-mail: \_\_\_\_\_

#### 3. LOCATION OF UNDERTAKING (describe and attach a topographical map, indicating the main components of the Undertaking)

FOX-3 (Dewar Lakes) is situated in Nunavut on Baffin Island north of Dewar Lakes. It is located on a hill top, about 518 m above sea level, in an area of general glacial scouring and eskers. The airstrip in the valley is approximately 152 m above sea level. The closest source of support is FOX-M, Hall Beach to the west. Flight time from FOX-M to FOX-3 is 3 hours (including a half hour refueling stop) by helicopter under normal conditions. A helipad is located on-site, as well as an abandoned airstrip which may be useable.

See Annex A for the FOX-3 Site Plan Drawings (Serial H-D67/2-8400-101 and Serial H-D67/2-8400-102).

Latitude: (68°40'48''N) Longitude: (71°14'48''W)      NTS Map Sheet No. N.A.      Scale: N.A.

#### 4. DESCRIPTION OF UNDERTAKING (attach plans and drawings)

FOX-3 is a Long Range Radar Site (LRR) for the North Warning System (NWS). FOX-3 is an unmanned site, but it is visited by FOX-M staff on scheduled quarterly preventive and corrective maintenance trips and on an as needed basis. During the months of May to September there may be an average of 5 to 20 personnel on-site due to seasonal project activity and occasional Third Party visitors.

FOX-3 is one of 11 LRRs of the North Warning System (NWS). The Prime Mission of the radar sites is to gather information about any airborne activity within their coverage area. The LRRs are located across the Yukon, Northwest Territories, Nunavut, and down the Labrador coast. The facilities are remotely monitored and controlled from North Bay on a 24/7 basis. The information they receive is automatically sent to the Canadian Air Defence Sector located at 22 Wing, CFB North Bay over a long-haul satellite communications network.

See Annex A for the FOX-3 Site Plan Drawings (Serial H-D67/2-8400-101 and Serial H-D67/2-8400-102).

5. **TYPE OF PRIMARY UNDERTAKING** (A supplementary questionnaire must be submitted with the application for undertakings listed in “**bold**”)

<input type="checkbox"/> Industrial	<input type="checkbox"/> Agricultural
<input type="checkbox"/> Mining and Milling (includes exploration/drilling)	<input type="checkbox"/> Conservation
<input checked="" type="checkbox"/> Municipal (includes camps/lodges)	<input type="checkbox"/> Recreational
<input type="checkbox"/> Power	<input type="checkbox"/> Miscellaneous (describe below):

See Schedule II of *Northwest Territories Waters Regulations* for Description of Undertakings

6. **WATER USE**

<input checked="" type="checkbox"/> To obtain water	<input type="checkbox"/> Flood control
<input type="checkbox"/> To cross a watercourse	<input type="checkbox"/> To divert a watercourse
<input type="checkbox"/> To modify the bed or bank of a watercourse	<input type="checkbox"/> To alter the flow of, or store, water
<input type="checkbox"/> Other (describe):	

7. **QUANTITY OF WATER INVOLVED** (cubic metres per day including both quantity to be used and quality to be returned to source)

Water use  100m<sup>3</sup>/day or less \*

Greater than 100m<sup>3</sup>/day; if greater, indicate quantities to be used for each purpose (camp, drilling, etc.)

\* Water use varies depending on the number of people on-site, i.e. from 0 m<sup>3</sup>/day (unmanned status) to a maximum of 2.9 m<sup>3</sup>/day (height of seasonal activity, ramped up site at full capacity). The seasonal activity from May to September varies from year to year; one season may have no projects, while the next season's projects may have the site at full capacity.

Please note that water is not drawn from the water lake daily. The site has four 10 m<sup>3</sup> (10,000 liter) raw water tanks. When the water in the tanks reaches a low level, an alarm alerts Nasittuq staff to fill the tanks with water from the water lake.

In order to fill up the four water tanks in one day and in order to meet the peak seasonal demand of a ramped up site, potentially at full capacity, Nasittuq requests a licence that allows the drawing of 40 m<sup>3</sup>/day (40,000 liters/day) up to three times in a month. This totals 120 m<sup>3</sup> (120,000 liters) in a 31-day month. This is less than half of the water usage currently allowed (310 m<sup>3</sup> in a 31-day month, drawn at 10 m<sup>3</sup>/day) by the site's Licence NWB6FOD0409 – Type “B”. Please note that the filling of the water tanks up to three times in a month is only a potential seasonal occurrence if the site is at full capacity. When the site is unmanned, and only quarterly preventive/corrective maintenance visits occur, the water usage is greatly reduced and the raw water tanks may be filled up to three times during the entire period between October and April.

Nasittuq requests a licence that requires the recording of the daily quantity of raw water drawn from the water lake. We wish to confirm that the monitoring point for the water intake, FOD-1, is the flow meter installed inside the building train in the fill line to the raw water tanks and is not at the intake at the water lake itself. The flow meter was installed at this location for ease of reading and maintenance. We trust this is acceptable.

Water returned to source:      Quality returned:

0 m<sup>3</sup>/day      While no raw water or unused treated water is returned to the source (the water lake), sewage (blackwater) and greywater are discharged to the environment via a sewage outfall pipe. Please see “Sewage” in Item 8 below for more information.

8. **WASTE** (for each type of waste describe: composition, quantity (cubic metres per day), methods of treatment and disposal, etc.)

**Sewage** - Sewage (blackwater) and greywater are combined in the sewage system. The sewage system comprises a sump, holding tank, and masticating pump within the building train, and a sewage outfall pipe leading to an outfall area on the land. This system has been in place since 1957. In 1995, the site changed from manned to unmanned status. Since then the site is visited by CAM-M staff on scheduled quarterly preventive and corrective maintenance trips and on an as needed basis. Little sewage is generated during these visits. During the months of May to September the site may be returned to manned status (ramped up) to support project activity. The amount of sewage depends on the number of people on-site.

Sewage is not discharged daily. When the sewage tank nears or reaches capacity, the sewage is discharged out the sewage outfall pipe to the designated outfall area. Up to 10 m<sup>3</sup> is discharged at one time from two to five times a year, depending on the number of people that have visited the site.

The site has one incinerating toilet which reduces sewage to ash; the ash is disposed of in the approved landfill. The incinerating toilet's cycling time (interval between usage) does not make it practical to support anything but a short site visit by a few staff. It is primarily in place in case the site fails in the winter and freezes. Under these conditions, a small crew would be dispatched to the site to restore power and thaw the site. The incinerating toilet would be used until the sewage system was thawed and returned to a serviceable state. It cannot meet the demands of a ramped up site.

We request the sewage effluent sampling be done during the month when the site is ramped up when there is active discharge, or a minimum once annually during those years when there is no ramp-up. The sampling point is FOD-2, the end of the sewage outfall pipe, as shown in Annex A FOX-3 Site Plan Drawing (Serial No. H-D67/2-8400-2).

Sewage effluent samples will be analyzed for:

- a) Biochemical Oxygen Demand (BOD), total suspended solids (TSS), fecal coliforms, pH, phenols, and oil & grease;
- b) total arsenic, total copper, total iron, total mercury, total zinc, sulphate, total cadmium, total chromium, total lead, and total nickel; and
- c) nitrate-nitrite, sodium, magnesium, conductivity, ammonia nitrogen, potassium, and calcium.

**Solid Waste** - Nonhazardous, combustible solid waste is typically paper, paper products, cardboard, rags, kitchen waste, etc. The quantity depends on the number of people on-site and the amount of this type of waste generated by project activity during a given year, but an estimate would be 32 m<sup>3</sup> for a year that included a ramped up site at capacity for two months. This type of solid waste will be incinerated by an incinerator. Ash from the incinerator will be disposed of in the approved landfill. Nasittuq will strive to achieve compliance with the Canada-Wide Standards for Mercury Emissions and Canada-Wide Standards for Dioxins and Furans by separating out and not incinerating waste that may generate hazardous emissions such as treated wood, plastics, rubber, electrical wire, hazardous materials, and articles containing hazardous materials.

Nonhazardous, noncombustible solid waste will be disposed of in the approved landfill.

**Hazardous** - Hazardous waste is retrograded to a licensed disposal facility located outside of Nunavut every one or two years.

**Bulky Items/Scrap Metal** - These items are stored on a pallet line and retrograded for disposal outside of Nunavut as required, typically every two to four years.

**Waste oil** - Waste oil is retrograded to a licensed disposal facility located outside of Nunavut every one or two years.

**Greywater** - Sewage (blackwater) and grey water are both handled by the sewage system described above. Please see "Sewage" above.

**8. WASTE (continued)**

Sludges  
 Other describe:

**9. OTHER PERSONS OR PROPERTIES AFFECTED BY THIS UNDERTAKING** (give name, mailing address and location; attach if necessary)

Not applicable. Department of National Defence property.

**Land Use Permit**

DIAND  Yes  No If no, date expected \_\_\_\_\_

Regional Inuit Association  Yes  No If no, date expected \_\_\_\_\_

Commissioner  Yes  No If no, date expected \_\_\_\_\_

**10. PREDICTED ENVIRONMENTAL IMPACTS OF UNDERTAKING AND PROPOSED MITIGATION MEASURES** (direct, indirect, cumulative impacts, etc.)

Nasittuq Corp., North Warning System (NWS) Project, has maintained an Environmental Management System (EMS) registered to the ISO 14001:2004 EMS standard since 2006. As part of its EMS, Nasittuq completed a systematic review of the activities required to operate and maintain the North Warning System sites and identified those activities which could have an impact on the environment. For each such activity, Nasittuq identified the potential negative environmental impacts and associated preventive and mitigative measures. These measures include implementation of company policies, plans, and procedures; training – both company developed courses and on-the-job training to ensure employees know their responsibilities; and annual audits of site activities to ensure company requirements are followed. As well, Nasittuq continuously reviews legal and other requirements to ensure that activities are conducted in accordance with current acts and regulations.

Nasittuq Corp.'s main environmental document is the Environmental Protection Plan (EPP). The EPP contains Nasittuq's Environmental Policy which states Nasittuq's commitment to environmental stewardship and outlines Nasittuq's contractual requirements with the Department of National Defence and the responsibilities of Nasittuq employees and subcontractors. The EPP states procedures for environmental practices at NWS sites in the following areas: wildlife; heritage resource protection; water supply management and treatment; vehicle movement and maintenance; roads, ground, and helipads; solid waste management; waste water management; hazardous materials management; halocarbon management; waste hazardous materials management; spill contingency plan; and environmental assessments. As well, background information is provided in the form of: NWS site descriptions, legal and other requirements, environmental aspects and impacts, and regional environments and wildlife, including species at risk.

While the regular operation and maintenance (day-to-day) activities of the NWS and the prevention/mitigation of potential environmental impacts are addressed by the EMS and EPP, one-time Additional Work Requirement (AWR) projects undergo an environmental assessment during the design phase to identify the unique impacts and required preventive/mitigative measures to be applied for the duration of the project.

NIRB Screening  Yes  No If no, date expected \_\_\_\_\_  
Not applicable.

**11. INUIT WATER RIGHTS**

Will the project or activity substantially affect the quality, quantity, or flow of water flowing through Inuit Owned Lands and the rights of Inuit under Article 20 of the Nunavut Land Claims Agreement?

If yes, has the applicant entered into an agreement with the Designated Inuit organization to pay compensation for any loss or damage that may be caused by the alteration. If no compensation agreement has been made, how will compensation be determined?

**The project will not substantially affect the quality, quantity, or flow of water through Inuit Owned Lands.**

**12. CONTRACTORS AND SUB-CONTRACTORS (name, address and functions)**

Nasituq Corporation

Suite 100, 170 Laurier Avenue West

Ottawa, ON K1P 5V5

(Contractor for the operation and maintenance of the North Warning System)

**13. STUDIES UNDERTAKEN TO DATE (list and attach copies of studies, reports, research, etc.)**

Initial Environmental Evaluation of the North Warning System Project Eleven Long Range Radar Sites and the Short Range Radar Development Site, Volume One. Monenco-Eyretechnics Group, October 1987  
(attached as Annex B).

**14. THE FOLLOWING DOCUMENTS MUST BE INCLUDED WITH THE APPLICATION FOR THE REGULATORY PROCESS TO BEGIN**

Supplementary Questionnaire (where applicable: see section 5)  Yes  No If no, date expected \_\_\_\_\_

Inuktitut and/or Inuinnaqtun/English Summary of Project  Yes  No If no, date expected \_\_\_\_\_

Application fee of \$30.00 (Payee Receiver General for Canada)  Yes  No If no, date expected \_\_\_\_\_

Water Use fee of \$30.00 (unless otherwise indicated in Section 9 of the *NWT Waters Regulations*; Payee Receiver General for Canada)  Yes  No If no, date expected \_\_\_\_\_

**15. PROPOSED TIME SCHEDULE (unless otherwise indicated, the NWB will consider the application for a five (5) year term)**

one year or less (or)  Multi Year

Start Date: 1950's Completion Date: 2030

JACQUES PIANTE / PRESIDENT  
Name (Print) Title (Print)

  
Signature

30 SEPT. 2008  
Date

For Nunavut Water Board office use only

APPLICATION FEE Amount: \$ \_\_\_\_\_ Pay ID No.: \_\_\_\_\_

WATER USE DEPOSIT Amount: \$ \_\_\_\_\_ Pay ID No.: \_\_\_\_\_

## **Annex A**

### **FOX-3 Site Plan Drawings**

- Serial H-D67/2-8400-101
- Serial H-D67/2-8400-102



P.O. Box 119  
GJOA HAVEN, NU X0B 1J0  
TEL: (867) 360-6338  
FAX: (867) 360-6369

ᓇᓱᑦ ሀᓂᓱᑦ ንᓂጀጀ  
NUNAVUT WATER BOARD  
NUNAVUT IMALIRIYIN KATIMAYINGI  
OFFICE DES EAUX DU NUNAVUT

## EXPLORATION/ REMOTE CAMP SUPPLEMENTARY QUESTIONNAIRE

**Applicant:** Nasittuq Corporation      **Licence No:** \_\_\_\_\_  
(For NWB Use Only)

### ADMINISTRATIVE INFORMATION

1. Environment Manager: Scott Charland Tel: 613-234-9033 ext. 626 Fax: 613-234-2671  
E-mail: scott.charland@nasittuq.com
  
2. Project Manager: Jacques Plante Tel: 613-234-9033 ext. 833 Fax: 613-234-2671  
E-mail: jacques.plante@nasittuq.com
  
3. Does the applicant hold the necessary property rights? No.
  
4. Is the applicant an 'operator' for another company (i.e., the holder of the property rights)? If so, please provide letter of authorization.

Please see attached **Annex A** which contains the authorization in:

- a. the letter dated 06 December 2007, Serial No. NWS-0757, to Ms Dionne Fillatrault, Director of Licensing, Nunavut Water Board from Ms Nancy Morin, Supply Team Leader/NWS Contract Authority, North Warning System.

The second paragraph explains that Nasittuq was awarded a contract by Canada to operate and maintain the North Warning System (NWS) in November 2001 and that "possession, care, custody and control over the NWS passed from Canada to Nasittuq"; and

- b. Article A2 Infrastructure and Scope of Work for the North Warning System Operation and Maintenance (excerpt from Contract Serial No. W8485-98RH01/01-NX).  
Paragraph 3 states "As of the Effective Date {of the contract}, possession and control over the North Warning System as defined in the SOW {Statement of Work} shall pass from the Crown over to the Contractor who shall have care and custody of the same."

5. Duration of the Project

One year or less      Start and completion dates: \_\_\_\_\_  
 Multi Year:

If Multi-Year indicate proposed schedule of on site activities  
Start: 1950's Completion: 2030

## CAMP CLASSIFICATION

### 6. Type of Camp

- Mobile (self-propelled)
- Temporary
- Seasonally Occupied: \_\_\_\_\_
- Permanent
- Other: National Defence Long Range Radar Site.

### 7. What is the design, maximum and expected average population of the camp?

FOX-3 (Dewar Lakes) is a Long Range Radar Site (LRR) for the North Warning System (NWS). FOX-3 is an unmanned site, but it is visited by FOX-M staff on scheduled quarterly preventive and corrective maintenance trips and on an as needed basis. During the months of May to September there may be an average of 5 to 20 personnel on-site due to seasonal project activity and occasional Third Party visitors.

### 8. Provide history of the site if it has been used in the past.

FOX-3 was built in the 1950's as one of the Distant Early Warning Line (DEW Line) radar sites which stretched from Alaska to Greenland. In the 1980's, the DEW Line in Canada evolved into the North Warning System (NWS) with radar sites extending from the Yukon across the Arctic and down the Labrador coast. FOX-3 was modernized as part of this transition. On 29 August 1995, the site changed from manned to unmanned status. Over the years, the Prime Mission of the radar sites remains unchanged: to detect airborne objects within the Arctic surveillance area.

FOX-3 is a Long Range Radar (LRR) site. FOX-3's facilities include site buildings with their integral mechanical and electrical systems, power generation system, fuel tanks, radar, antennas, satellite ground terminals, weather equipment, and roads.

## CAMP LOCATION

### 9. Please describe proposed camp location in relation to biogeographical and geomorphological features, and water bodies.

FOX-3 is situated in Nunavut on Baffin Island north of Dewar Lakes. It is located on a hill top, about 518 m above sea level, in an area of general glacial scouring and eskers. The airstrip in the valley is approximately 152 m above sea level. The geographical coordinates are: 68 40' 48" N, 71 14' 48" W.

The hill top (about 518 m asl) is in an area indicating general glacial scouring. Surface materials include bedrock, till and fluvial materials, with till being the most common. The area is strewn with boulders up to 1 meter across. The airstrip area features fluvial deposits of gravels, sands, and silts. Vegetation is relatively scarce with some patches of wood rush, grass, and wildflowers. The wetter areas may consist of sedges and moss.

The most prominent topographical features include rolling hills, separated by broad intervening depressions, and an interconnecting lake system running through a deep valley.

Vegetation is sparse and more suitable for birds than larger grazing mammals. However, a small group of caribou from the Baffin Island herd occasionally wanders through the Dewar Lakes area, although the herd is generally located farther west. Arctic foxes and wolves are also occasionally seen at FOX-3.

Waterfowl that nest in small shallow ponds in the area include the red-throated loon, tundra swan, greater snow goose, king eider and oldsquaw. To the south and west of the site are colonies of Sabine's gulls.

10. How was the location of the camp selected? Was the site previously used? Was assistance from the Regional Inuit Association Land Manager sought? Include maps and/or aerial photographs.

The location of the site was based on the National Prime Mission (National Defence) requirements.

See attached **Annex B** FOX-3 Site Plan Drawings (Serial H-D67/2-8400-101 and Serial H-D67/2-8400-102) and attached **Annex C** FOX-3 Aerial Photo.

11. Is the camp or any aspect of the project located on:

<input checked="" type="checkbox"/> Crown Lands	Permit Number (s)/Expiry Date: <u>Not applicable</u>
<input type="checkbox"/> Commissioners Lands	Permit Number (s)/Expiry Date: _____
<input type="checkbox"/> Inuit Owned Lands	Permit Number (s)/Expiry Date: _____

12. Closest Communities (direction and distance in km):

The closest communities are:

- Broughton Island, 322 km (200 miles) to the east; and
- Hall Beach, 401 km (251 miles) to the west. Flight time from FOX-M (Hall Beach) to FOX-3 is 3 hours (including a half hour refueling stop) by helicopter under normal conditions.

13. Has the proponent notified and consulted the nearby communities and potentially interested parties about the proposed work?

Not applicable. The site is unmanned and is visited by Nasittuq employees based in FOX-M, Hall Beach. These employees include Hall Beach residents and northern hires from other communities. For seasonal work, job openings are posted in a variety of ways including ads in northern newspapers and on Nasittuq's website.

14. Will the project have impacts on traditional water use areas used by the nearby communities?  
Will the project have impacts on local fish and wildlife habitats?

No.

## PURPOSE OF THE CAMP

15.  Mining (includes exploration drilling)  
 Tourism (hunting, fishing, wildlife observation, adventure/expedition, etc.)  
 Other National Prime Mission (National Defence radar site)  
(therefore questions # 16 to 22 are not applicable.)

16. Activities (check all applicable)

**Not applicable – not a mining camp.**

Preliminary site visit  
 Prospecting  
 Geological mapping  
 Geophysical survey  
 Diamond drilling  
 Reverse circulation drilling  
 Evaluation Drilling/Bulk Sampling (also complete separate questionnaire)  
 Other: \_\_\_\_\_

17. Type of deposit (exploration focus):

**Not applicable – not a mining camp.**

Lead Zinc  
 Diamond  
 Gold  
 Uranium  
 Other: \_\_\_\_\_

## DRILLING INFORMATION

18. Drilling Activities

**Not applicable – not a mining camp.**

Land Based drilling  
 Drilling on ice

19. Describe what will be done with drill cuttings?

**Not applicable – not a mining camp.**

20. Describe what will be done with drill water?

**Not applicable – not a mining camp.**

21. List the brand names and constituents of the drill additives to be used? Includes MSDS sheets and provide confirmation that the additives are non-toxic and biodegradable.  
**Not applicable – not a mining camp.**

22. Will any core testing be done on site? Describe.  
**Not applicable – not a mining camp.**

## SPILL CONTINGENCY PLANNING

23. The proponent is required to have a site specific Spill Contingency Plan prepared and submitted with the application. This Plan should be prepared in accordance with the *NWT Environmental Protection Act, Spill Contingency Planning and Reporting Regulations, July 22, 1998* and *A Guide to the Spill Contingency Planning and Reporting Regulations, June 2002*. Please include for review.

Nasittuq's Spill Contingency Plan is attached as **Annex D**.

24. How many spill kits will be on site and where will they be located?

Two (2) spill kits are on-site in the Warehouse:

- the POL (petroleum, oil, lubricants) Spill; and
- the Chemical Spill Kit.

The locations are shown on **Annex B** FOX-3 Site Plan Drawing (Serial H-D67/2-8400-102).

25. Please describe the types, quantities, and method of storage of fuel and chemicals on site, and provide MSDS sheets.

Jet A1 is the fuel used on-site. Jet A1 fuel tanks and locations are listed below.

Tank Size	LOC ID	Actual Capacity*	Location	Type of fuel
69,200L	DEWW20A	64,860L	Power Plant	PGS
69,200L	DEWW20C	64,860L	Power Plant	PGS
246,000L	DEWW22C	208,116L	Summit	Aviation/PGS
246,000L	DEWW22D	208,116L	Summit	Aviation/PGS
246,000L	DEWW22E	208,116L	Apron	Aviation
69,200L	DEWW20D	64,860L	Apron	Aviation
69,200L	DEWW20E	64,860L	Apron	Aviation
<b>SUMMIT TOTAL</b>		545,952L		
<b>APRON TOTAL</b>		337,836L		
<b>TOTAL:</b>		883,788L		

Tanks: The total volume of usable fuel on site is 883,788L.

See **Annex E** for the Jet A1 MSDS.

Other items such as batteries, aerosols, and cleaning products are stored in the warehouse and in the buildings where they are used. Drums of oil and glycol and a limited number of cylinders are stored in the warehouse as shown on **Annex B** FOX-3 Site Plan Drawing (Serial H-D67/2-8400-102).

## **WATER SUPPLY AND TREATMENT**

26. Describe the location of water sources.

The water source is the lake. See **Annex B** FOX-3 Site Plan Drawing (Serial H-D67/2-8400-101).

27. Estimated water use (in cubic metres/day):

Domestic Use: up to 2.9 cubic metres/day Water Source: Water Lake  
during ramp up with site at full capacity  
 Drilling: \_\_\_\_\_ Water Source: \_\_\_\_\_  
 Other: \_\_\_\_\_ Water Source: \_\_\_\_\_

28. Describe water intake for camp operations? Is the water intake equipped with a mesh screen to prevent entrapment of fish? (see *DFO 1995, Freshwater Intake End-of-Pipe Fish Screen Guideline*) Describe:

Water from a natural fresh water lake is pumped into a water truck, then transferred to the site's raw water tanks. There is a screen on the water intake.

Water use varies depending on the number of people on-site, i.e. from 0 m<sup>3</sup>/day (unmanned status) to a maximum of 2.9 m<sup>3</sup>/day (height of seasonal activity, ramped up site at full capacity). The seasonal activity from May to September varies from year to year; one season may have no projects, while the next season's projects may have the site at full capacity.

Please note that water is not drawn from the water lake daily. The site has four 10 m<sup>3</sup> (10,000 liter) raw water tanks. When the water in the tanks reaches a low level, an alarm alerts Nasittuq staff to fill the tanks with water from the water lake.

In order to fill up the four water tanks in one day and in order to meet the peak seasonal demand of a ramped up site, potentially at full capacity, Nasittuq requests a licence that allows the drawing of 40 m<sup>3</sup>/day (40,000 liters/day) up to three times in a month. This totals 120 m<sup>3</sup> (120,000 liters) in a 31-day month. This is less than half of the water usage currently allowed (310 m<sup>3</sup> in a 31-day month, drawn at 10 m<sup>3</sup>/day) by the site's Licence NWB6FOD0409 – Type "B". Please note that the filling of the water tanks up to three times in a month is only a potential seasonal occurrence if the site is at full capacity. When the site is unmanned, and only quarterly preventive/corrective maintenance visits occur, the water usage is greatly reduced and the raw water tanks may be filled up to three times during the entire period between October and April.

Nasittuq requests a licence that requires the recording of the daily quantity of raw water drawn from the water lake. We wish to confirm that the monitoring point for the water intake, FOD-1, is the flow meter installed inside the building train in the fill line to the raw water tanks and is not at the intake at the water lake itself. The flow meter was installed at this location for ease of reading and maintenance. We trust this is acceptable.

29. Will drinking water quality be monitored? What parameters will be analyzed and at what frequency?

Yes, the drinking water quality is monitored on a quarterly basis and monthly basis when site is ramped up. Bacteriological water test is performed at two locations on site to be determined by site technicians. Both samples are taken from regular consumption and food preparation areas. The bacteriological tests check the water for *E. coli* and Total Coliforms. A Heterotrophic Plate Count (HPC) is also done. All must pass for the water to be consumed.

On an annual basis a chemical water sample analysis is performed by an outside testing facility. Two samples are taken: one from the water source (lake) and one from a point of consumption inside the building. The samples are shipped to a testing facility where they test for the physical and chemical water properties listed below.

**Physical and Chemical Parameters:**

Alkalinity	Hardness	Phenols
Ammonia	Hydrogen sulphide	Potassium
BOD5	Iron	Sodium
Calcium	Magnesium	Sulphate
Chloride	Manganese	Tannin and lignin
Colour	Nitrate	Total Dissolved Solids
Conductivity	Nitrite	Total Kjeldahl Nitrogen (TKN)
Chemical Oxygen Demand	PCBs	Turbidity
Fluoride	pH	

**Bacteriological Parameters:**

<i>E. coli</i>	Heterotrophic Plate Count (HPC)
Fecal streptococci	Total and Fecal coliforms

30. Will drinking water be treated? How?

The drinking water is treated by sediment filters, granular activated carbon filters and an ultraviolet (UV) filtration system.

31. Will water be stored on site?

Raw (untreated) water is stored in four 10,000 liter raw water storage tanks next to the monitoring point, FOD-1 (the flow meter in the fill line to the raw water tanks). See **Annex B** FOX-3 Site Plan Drawing (Serial H-D67/2-8400-102).

Treated drinking water is piped directly to water taps.

## WASTE TREATMENT AND DISPOSAL

32. Describe the characteristics, quantities, treatment and disposal methods for:

Camp Sewage (blackwater)

Sewage (blackwater) and greywater are combined in the sewage system. The sewage system comprises a sump, holding tank, and masticating pump within the building train, and a sewage outfall pipe leading to an outfall area on the land. This system has been in place since 1957. In 1995, the site changed from manned to unmanned status. Since then the site is visited by FOX-M staff on scheduled quarterly preventive and corrective maintenance trips and on an as needed basis. Little sewage is generated during these visits. During the months of May to September the site may be returned to manned status (ramped up) to support project activity. The amount of sewage depends on the number of people on-site.

Sewage is not discharged daily. When the sewage tank nears or reaches capacity, the sewage is discharged out the sewage outfall pipe to the designated outfall area. Up to 10 m<sup>3</sup> is discharged at one time from two to five times a year, depending on the number of people that have visited the site.

The site has one incinerating toilet which reduces sewage to ash; the ash is disposed of in the approved landfill. The incinerating toilet's cycling time (interval between usage) does not make it practical to support anything but a short site visit by a few staff. It is primarily in place in case the site fails in the winter and freezes. Under these conditions, a small crew would be dispatched to the site to restore power and thaw the site. The incinerating toilet would be used until the sewage system was thawed and returned to a serviceable state. It cannot meet the demands of a ramped up site.

We request the sewage effluent sampling be done during the month when the site is ramped up when there is active discharge, or a minimum once annually during those years when there is no ramp-up. The sampling point is FOD-2, the end of the sewage outfall pipe, as shown in **Annex B FOX-3 Site Plan Drawing** (Serial H-D67/2-8400-102).

Sewage effluent samples will be analyzed for:

- a) Biochemical Oxygen Demand (BOD), total suspended solids (TSS), fecal coliforms, pH, phenols, and oil & grease;
- b) total arsenic, total copper, total iron, total mercury, total zinc, sulphate, total cadmium, total chromium, total lead, and total nickel; and
- c) nitrate-nitrite, sodium, magnesium, conductivity, ammonia nitrogen, potassium, and calcium.

Camp Greywater

Grey water and sewage (blackwater) are both handled by the sewage system described above. Please see "Camp Sewage (blackwater)" above.

32. Continued

Solid Waste

Nonhazardous, combustible solid waste is typically paper, paper products, cardboard, rags, kitchen waste, etc. The quantity depends on the number of people on-site and the amount of this type of waste generated by project activity during a given year, but an estimate would be 32 m<sup>3</sup> for a year that included a ramped up site at capacity for two months. This type of solid waste will be incinerated by an incinerator. Ash from the incinerator will be disposed of in the approved landfill. Nasittuq will strive to achieve compliance with the Canada-Wide Standards for Mercury Emissions and Canada-Wide Standards for Dioxins and Furans by separating out and not incinerating waste that may generate hazardous emissions such as treated wood, plastics, rubber, electrical wire, hazardous materials, and articles containing hazardous materials.

Nonhazardous, noncombustible solid waste will be disposed of in the approved landfill.

Bulky Items/Scrap Metal

These items are stored on a pallet line and retrograded for disposal outside of Nunavut as required, typically every two to four years.

Waste Oil/Hazardous Waste

These items are retrograded to a licensed disposal facility located outside of Nunavut every one or two years.

An average annual retrograde typically includes:

- 12 drums Waste oil
- 2 drums Waste glycol
- 11 drums Waste fuel
- 1 drum Waste paint
- 1 drum Waste oil filters
- 1 crate Waste batteries, wet, filled with acid
- 1 crate Waste batteries, nonspillable
- 1 cylinder Waste acetylene, dissolved
- 1 to 2 cylinders Waste refrigerant gases.

Empty Barrels/Fuel Drums

These items are re-used to contain the same liquids.

Other:

33. **Please describe incineration system if used on site. What types of wastes will be incinerated?**

The incinerator will be a forced air incinerator which reduces the waste to ash. The operation and maintenance of the incinerator will meet the criteria in the draft note entitled Incineration by the Nunavut Department of Environment forwarded from Mr. Bernie MacIsaac, Manager Field Operations, INAC-NRO, Iqaluit NU to Mr. Jacques Plante, Nasittuq Corp., Ottawa ON. As stated above in Item 32 Solid Waste, only waste that will not generate hazardous emissions will be incinerated. Typically this will be waste such as paper, paper products, cardboard, rags, kitchen waste, etc.

34. **Where and how will non-combustible waste be disposed of? If in a municipality in Nunavut, has authorization been granted?**

Non-combustible, nonhazardous waste will be disposed of in the approved landfill on-site. Non-combustible, hazardous waste is retrograded to a licensed disposal facility outside of Nunavut every one or two years.

35. **Describe location (relative to water bodies and camp facilities) dimensions and volume, and freeboard for all sumps (if applicable).**

Not applicable.

36. Will leachate monitoring be done? What parameters will be sampled and analyzed, and at what frequency?

Not applicable.

## **OPERATION AND MAINTENANCE**

37. Have the water supply and waste treatment and disposal methods been used and proven in cold climate? What known O&M problems may occur? What contingency plans are in place?

The water supply has been in use at the site by Nasittuq Corp. for many years and is proven in cold climates.

The sewage treatment and disposal methods have been used on-site by Nasittuq Corp. for many years and are proven in cold climates.

The incinerator will be a new method for the treatment of solid waste. However, Nasittuq will select an incinerator that will work in cold climates, such as the Smart Ash which is U.S. EPA approved for small batch incineration.

## ABANDONMENT AND RESTORATION

38. Provide a detailed description of progressive and final abandonment and restoration activities at the site.

Not applicable. The Prime Mission is scheduled to at least 2030. No abandonment or restoration is planned at this time.

## BASELINE DATA

39. Has or will any baseline information be collected as part of this project? Provide bibliography.

Physical Environment (Landscape and Terrain, Air, Water, etc.)  
 Biological Environment (Vegetation, Wildlife, Birds, Fish and Other Aquatic Organisms, etc.)  
 Socio-Economic Environment (Archaeology, Land and Resources Use, Demographics, Social and Culture Patterns, etc.)  
 Other: \_\_\_\_\_

### Bibliography:

Initial Environmental Evaluation of the North Warning System Project Eleven Long Range Radar Sites and the Short Range Radar Development Site, Volume One. Monenco-Eyretchnics Group, October 1987.

## REGULATORY INFORMATION

40. At a minimum, you should ensure you have a copy of and consult the documents below for compliance with existing regulatory requirements:

- ✓ ARTICLE 13 – *NCLA -Nunavut Land Claims Agreement*
- ✓ NWNSRTA – *The Nunavut Waters and Nunavut Surface Rights Tribunal Act, 2002*
- ✓ *Northwest Territories Waters Regulations, 1993*
- ✓ NWB - Water Licensing in Nunavut - Interim Procedures and Information Guide for Applicants
- ✓ NWB - Interim Rules of Practice and Procedure for Public Hearings
- ✓ RWED – *Environmental Protection Act, R-068-93- Spill Contingency Planning and Reporting Regulations, 1993*
- ✓ RWED A Guide to the Spill Contingency Planning and Reporting Regulations, 2002
- ✓ NWTWB - Guidelines for Contingency Planning
- ✓ *Canadian Environmental Protection Act, 1999 (CEPA)*
- ✓ *Fisheries Act, RS 1985 - s.34, 35, 36 and 37*
- ✓ DFO - Freshwater Intake End of Pipe Fish Screen Guideline
- ✓ NWTWB - Guidelines for the Discharge of Treated Municipal Wastewater in the NWT

40. Continued

- ✓ Canadian Council for Ministers of the Environment (CCME); Canadian Drinking Water Quality Guidelines, 1987
- ✓ Public Health Act - Camp Sanitation Regulations
- ✓ Public Health Act - Water Supply Regulations
- ✓ *Territorial Lands Act and Territorial Land Use Regulations*; Updated 2000