

NTCL also has a class II Icebreaker Supply Vessel located in Halifax which can be mobilized within 7-10 days to Baker Lake dependent on severe ice conditions. NTCL crews are very familiar with large scale oil pollution and have experience cleaning spills from the Terra Nova Platform offshore Newfoundland. In a large scale clean-up this vessel would be mobilized with oil recovery equipment located on the East Coast of Canada.



MSDS SHEETS

ARCTIC LOW SULPHUR DIESEL 310-112 Revision Number: 8



Shell Canada Limited Material Safety Data Sheet

Effective Date: 2005-11-07
Supersedes: 2002-11-06



Class B3 Combustible Class D2B Other Toxic Liquid Effects -Skin Irritant

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: **ARCTIC LOW SULPHUR DIESEL**
SYNONYMS: Automotive Gas Oil
PRODUCT USE: Fuel
MSDS Number: 310-112

SUPPLIER	TELEPHONE NUMBERS	
Shell Canada Limited P.O. Box 100, Station M 400-4th Ave. S.W. Calgary, AB Canada T2P 2H5	Shell Emergency Number CANUTEC 24 HOUR EMERGENCY NUMBER For general information: For MSDS information: (From 7:30 to 4:30 Mountain Time)	1-800-661-7378 613-996-6666 1-800-661-1600 403-691-3982 403-691-2220

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS Number	% Range	WHMIS Controlled
Fuels, Diesel, No. 2	68476-34-6	100	Yes

See Section 8 for Occupational Exposure Guidelines.

3. HAZARDS IDENTIFICATION

Physical Description: Liquid Lightly Coloured Hydrocarbon Odour

Routes of Exposure: Exposure will most likely occur through skin contact or inhalation. **Hazards:**

Vapour concentrations above the recommended exposure level are irritating to the eyes and respiratory tract, may cause headaches and dizziness, are anesthetic and may have other central nervous system effects.

Page 1 of 7

ARCTIC LOW SULPHUR DIESEL

310-112

Revision Number: 8

Combustible Liquid. Irritating to skin. Vapours are moderately irritating to the eyes.

Ingestion may result in vomiting. Avoid aspiration of vomitus into lungs as small quantities may result in aspiration pneumonitis.

Vapours are moderately irritating to the respiratory passages.

Handling: Eliminate all ignition sources. Avoid prolonged exposure to vapours. Wear suitable gloves and eye protection. Bond and ground transfer containers and equipment to avoid static accumulation. Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

For further information on health effects, see Section 11.

4. FIRST AID

4. FIRST AID

Eyes: Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.

Skin: Wash contaminated skin with mild soap and water for 15 minutes. If irritation occurs and persists, obtain medical attention.

Ingestion: DO NOT INDUCE VOMITING! OBTAIN MEDICAL ATTENTION IMMEDIATELY. Guard against aspiration into lungs by having the individual turn on to their left side. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs. Do not give anything by mouth to an unconscious person.

Inhalation: Remove victim from further exposure and restore breathing, if required. Obtain medical attention.

Notes to Physician: The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 mL/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

5. FIRE FIGHTING MEASURES

6. FIRE FIGHTING MEASURES

Extinguishing Media:	Dry Chemical Carbon Dioxide Foam Water Fog
Firefighting Instructions:	Caution -Combustible. Do not use a direct stream of water as it may spread fire. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus. Vapour forms a flammable/explosive mixture with air between upper and lower flammable limits. Vapours may travel along ground and flashback along vapour trail may occur. Avoid inhalation of smoke. Product will float and can be reignited on surface of water. Delayed lung damage can be experienced after exposure to combustion products, sometimes hours after the exposure.
Hazardous Combustion Products:	A complex mixture of airborne solid, liquid, particulates and gases will evolve when this material undergoes pyrolysis or combustion. Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed upon combustion.

Page 2 of

7

ARCTIC LOW SULPHUR DIESEL

310-112

Revision Number: 8

6. ACCIDENTAL RELEASE MEASURES

Issue warning "Combustible". Eliminate all ignition sources. Isolate hazard area and restrict access. Handling equipment must be grounded. Try to work upwind of spill. Avoid direct contact with material. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Dike and contain land spills; contain water spills by booming. Use water fog to knock down vapours; contain runoff. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Recommended materials: Clay or Sand Flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations. Notify appropriate environmental agency(ies).

7. HANDLING AND STORAGE

7. HANDLING AND STORAGE

Handling: Combustible. Avoid excessive heat, sparks, open flames and all other sources of ignition. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Vapours are heavier than air and will settle and collect in low areas and pits, displacing breathing air. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapours are gone. Vapours may accumulate and travel to distant ignition sources and flashback. Do not cut, drill, grind, weld or perform similar operations on or near containers. Empty containers are hazardous, may contain flammable/explosive dusts, residues or vapours. Do not pressurize drum containers to empty them. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing prior to reuse. Use good personal hygiene.

Storage: Store in a cool, dry, well ventilated area, away from heat and ignition sources. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

THE FOLLOWING INFORMATION, WHILE APPROPRIATE FOR THIS PRODUCT, IS GENERAL IN NATURE. THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT WILL VARY DEPENDING ON THE CONDITIONS OF USE.

OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):

Diesel fuel, as total hydrocarbons (skin): 100 mg/m³ Skin Notation: Absorption through skin, eyes and mucous membranes may contribute significantly to the total exposure.

Mechanical Ventilation: Concentrations in air should be maintained below the recommended threshold limit value if unprotected personnel are involved. Use explosion-proof ventilation as required to control vapour concentrations. Local ventilation recommended where mechanical ventilation is ineffective in controlling airborne concentrations below the recommended occupational exposure limit. Make up air should always be supplied to balance air exhausted (either generally or locally). For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Chemical safety goggles and/or full face shield to protect eyes and face, if product is handled such that it could be splashed into eyes. Provide an eyewash station in the area.

Page 3 of 7

ARCTIC LOW SULPHUR DIESEL 310-112

Revision Number: 8

Skin Protection: Impervious gloves (viton, nitrile) should be worn at all times when handling this material. In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.

Respiratory Protection: If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges or use a NIOSH-approved supplied-air respirator. For high airborne concentrations, use a NIOSH-approved supplied-air respirator, either self-contained or airline breathing apparatus, operated in positive pressure mode.

9. PHYSICAL DATA

Physical State: Liquid **Appearance:** Lightly Coloured **Odour:** Hydrocarbon **Odour Threshold:** Not available **Freezing/Pour Point:** Varies with region and season **Boiling Point:** 150 -330 °C **Density:** < 881 kg/m³ @ 15 °C **Vapour Density (Air = 1):** Not available **Vapour Pressure (absolute):** Not available **pH:** Not applicable **Flash Point:** Pensky-Martens CC > 40 °C **Lower Explosion Limit:** 1 % (vol.) **Upper Explosion Limit:** 6 % (vol.) **Autoignition Temperature:** 250 °C **Viscosity:** 1.7-3.6cSt @40°C **Evaporation Rate (n-BuAc = 1):** Not available **Partition Coefficient (log KOW):** Not available **Water Solubility:** Insoluble **Other Solvents:** Hydrocarbon **Solvents Formula:** C10 to C22 Hydrocarbons

10. STABILITY AND REACTIVITY

Chemically Stable:	Yes
Hazardous Polymerization:	No
Sensitive to Mechanical Impact:	No
Sensitive to Static Discharge:	Yes
Hazardous Decomposition Products:	Thermal decomposition products are highly dependent on combustion conditions.
Incompatible Materials:	Avoid strong oxidizing agents.
Conditions of Reactivity:	Avoid excessive heat, open flames and all ignition sources.

11. TOXICOLOGICAL INFORMATION

Ingredient (or Product if not specified)	Toxicological Data
Fuels, Diesel, No. 2	LD50 Dermal Rabbit > 5000 mg/kg LD50 Oral Rat = 9000 mg/kg

Routes of Exposure: Exposure will most likely occur through skin contact or inhalation. Page 4 of 7
ARCTIC LOW SULPHUR DIESEL

310-112

Revision Number: 8

Irritancy:

This product is expected to be irritating to skin but is not predicted to be a skin sensitizer.

Acute Toxicity:

Vapour concentrations above the recommended exposure level are irritating to the eyes and respiratory tract, may cause headaches and dizziness, are anesthetic and may have other central nervous system effects.

Chronic Effects:

Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea, blurred vision and central nervous system depression.

Pre-existing Conditions:

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

Carcinogenicity and Mutagenicity:

The International Agency for Research on Cancer (IARC) considers that this product is not classifiable as to its carcinogenicity to humans. Middle distillates have caused skin cancers in laboratory animals when applied repeatedly and left in place between applications. This effect is believed to be caused by the continuous irritation of the skin. Good personal hygiene should be maintained to avoid this risk. The American Conference of Governmental Industrial Hygienists (ACGIH) has classified this product as A3 -confirmed animal carcinogen with unknown relevance to humans.

12. ECOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May cause physical

fouling of aquatic organisms.

Biodegradability:

Bioaccumulation: Partition Coefficient (log KOW): Not readily biodegradable. Potential for bioaccumulation. Not available

Aquatic Toxicity May be harmful to aquatic life.

Ingredient:

Toxicological Data Fuels, Diesel, No. 2

EL50 -growth rate Algae (72hr) 10 -100 mg/L.

EL50 Daphnia Magna (48hr) 10 -100 mg/L.

LL50 (WAF method) Rainbow Trout (96hr) 10 -100 mg/L.

Definition(s):

LL and EL are the lethal loading concentration and effective loading concentration respectively. The concentration represents the amount of substance added to the system to obtain a toxic concentration. They replace the traditional LC and EC for low solubility substances. WAF is the water accommodated fraction. A slightly soluble hydrocarbon is

stirred into water and the insoluble portions are removed. The remaining solution is the water accommodated fraction.

13. DISPOSAL CONSIDERATIONS

13. DISPOSAL CONSIDERATIONS

Page 5 of 7

ARCTIC LOW SULPHUR DIESEL 310-112 Revision Number: 8

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery (cement kilns, thermal power generation), 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority.

14. TRANSPORTATION INFORMATION

14. TRANSPORTATION INFORMATION

Canadian Road and Rail Shipping Classification:

UN Number	UN1202
Proper Shipping Name	DIESEL FUEL
Hazard Class	Class 3 Flammable Liquids
Packing Group	PG III
Additional Information	Not Regulated in Containers Less Than or Equal to 450 Litres.
Shipping Description	DIESEL FUEL Class 3 UN1202 PG III Not Regulated in Containers Less Than or Equal to 450 Litres.

15. REGULATORY INFORMATION

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Class: Class B3 Combustible Liquid
Class D2B Other Toxic Effects -Skin Irritant

DSL/NDSL Status: This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act. This product and/or all components are listed on the U.S. EPA TSCA Inventory.

Other Regulatory Status: No Canadian federal standards.

16. ADDITIONAL INFORMATION

16. ADDITIONAL INFORMATION

LABEL STATEMENTS

Hazard Statement : Combustible Liquid.

Handling Statement: Irritating to skin.
Eliminate all ignition sources.
Avoid prolonged exposure to vapours.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

First Aid Statement : Wash contaminated skin with soap and water.
Flush eyes with water.
If overcome by vapours remove to fresh air.
Do not induce vomiting.
Obtain medical attention.

MSDS sheets are located onboard both vessels and will give necessary information for any other small quantities of lub oils or other hydraulic fluids and hazardous materials which might be located inside the barge engine room spaces and tug spaces. There is no risk of external spills of these pollutants but in the case of personnel exposure these MSDS sheets should be referenced.

MATERIAL SAFETY DATA SHEET

PENNZOIL® GEO PREMIUM ENGINE OIL - ALL GRADES

1. PRODUCT AND COMPANY IDENTIFICATION

MSDS Number: 13231

Version Date: 05/25/01

Product Name: PENNZOIL® GEO PREMIUM ENGINE OIL - ALL GRADES

Product Use: No information available

Synonyms: 30, 40, 15W-40

Company Information

SOPUS Products
P.O. Box 4427
Houston, TX 77210-4427
USA

Phone Numbers

Medical Emergency: 1-800-546-6040
Transportation Emergency (USA): 1-800-424-9300
Transportation Emergency (International):
1-703-527-3887 (Call Collect)
MSDS Assistance: 1-800-546-6227
Fax On Demand: 1-800-546-6227
Technical Assistance: 1-800-458-4998
Customer Service: 1-800-468-8397
Fax Number: 713-217-3181
Internet Address: www.MSDS.PZLQS.com

2. COMPONENT INFORMATION

Component	CAS No.	Weight Percent Range	Hazardous in Blend
BASE LUBRICATING OILS	MIXTURE	75 - 95	No
DETERGENT/INHIBITOR SYSTEM	MIXTURE	5 - 15	No
VISCOSITY INDEX IMPROVER	MIXTURE	< 10	No
POUR POINT DEPRESSANT	MIXTURE	< 1	No

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Other: No information available

3. HAZARDS IDENTIFICATION

Emergency and Hazards Overview

CAUTION: Contains Petroleum Lubricant. Repeated skin contact can cause skin disorders.

ATTENTION: Used motor oil is a possible skin cancer hazard based on animal data. Repeated exposure to oil mist in excess of the OSHA limit (5mg/m³) can result in accumulation of oil droplets in pulmonary tissue.

NFPA Ratings: Health 1 Flammability 1 Reactivity 0

Primary Route of Exposure: Skin X Inhalation -- Eye --

Health Effect Information

Eye Contact: This product is practically non-irritating to the eyes upon direct contact. Based on testing of similar products and/or components.

Skin Contact: Avoid skin contact. This product is minimally irritating to the skin upon direct contact.

Based on testing of similar products and/or components. Prolonged or repeated contact may result in contact dermatitis which is characterized by dryness, chapping, and reddening. Prolonged or repeated contact may result in oil acne which is characterized by blackheads with possible secondary infection. Avoid prolonged and repeated skin contact with used motor oils. See Section 11 - Toxicological Information.

MATERIAL SAFETY DATA SHEET

MSDS Number: 13231

PENNZOIL® GEO PREMIUM ENGINE OIL - ALL GRADES

Page 2 of 8

Inhalation: This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. On rare occasions, prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. Signs of respiratory effects vary with concentration and length of exposure and include nasal discharge, sore throat, coughing, bronchitis, pulmonary edema and difficulty breathing. Shortness of breath and cough are the most common symptoms.

Ingestion: Do not ingest. This product is relatively non-toxic by ingestion. This product has laxative properties and may result in abdominal cramps and diarrhea. Exposure to a large single dose, or repeated smaller doses, may lead to lung aspiration, which can lead to lipid pneumonia or chronic lung inflammation. These are low-grade, chronic localized tissue reactions.

Medical Conditions Aggravated by Exposure: Drying and chapping may make the skin more susceptible to other irritants, sensitizers and disease.

Other: No information available

4. FIRST AID INFORMATION

Eye Contact: Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If material is hot, treat for thermal burns and seek immediate medical attention.

Skin Contact: No treatment is necessary under ordinary circumstances. Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs and persists, seek medical attention. If material is hot, submerge injured area in cold water. If victim is severely burned, remove to a hospital immediately.

Inhalation: This material has a low vapor pressure and is not expected to present an inhalation exposure at ambient conditions.

Ingestion: No treatment is necessary under ordinary circumstances. Do not induce vomiting. If victim exhibits signs of lung aspiration such as coughing or choking, seek immediate medical assistance.

Notes to Physician: No information available

Other: No information available

5. FIRE AND EXPLOSION INFORMATION

Flammable Properties

Flash Point: >350 F, >176.7 C

Test Method: ASTM D-92 (C.O.C.)

Flammable Limits in Air

Upper Percent: No data available

Lower Percent: No data available

Autoignition Temperature: >900 F, >482.2 C

Test Method: No information available

NFPA Classification: Class III-B combustible liquid

Extinguishing Media: Use dry chemical, foam, or carbon dioxide.

Fire Fighting Measures

Special Fire Fighting Procedures and Equipment: Water may be ineffective but can be used to cool containers exposed to heat or flame to prevent vapor pressure buildup and possible container rupture. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

MATERIAL SAFETY DATA SHEET

MSDS Number: 13231

PENNZOIL® GEO PREMIUM ENGINE OIL - ALL GRADES

Page 3 of 8

Unusual Fire and Explosion Conditions: Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

Hazardous Combustion By-Products: None

Other: No information available

6. ACCIDENTAL RELEASE MEASURES

Personnel Safeguards: Consult Health Effect Information in Section 3, Personal Protection Information in Section 8, Fire and Explosion Information in Section 5, and Stability and Reactivity Information in Section 10.

Regulatory Notifications: Notify appropriate authorities of spill.

Containment and Clean up: Contain spill immediately. Do not allow spill to enter sewers or watercourses. Absorb with appropriate inert material such as sand, clay, etc. Large spills may be picked up using vacuum pumps, shovels, buckets, or other means and placed in drums or other suitable containers.

Other: No information available

7. HANDLING AND STORAGE INFORMATION

Handling: Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106-- Flammable and Combustible Liquids.

Storage: Do not transfer to unmarked containers. Store in closed containers away from heat, sparks, open flame, or oxidizing materials.

Empty Container Warnings

Drums: Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed. Empty containers retain product residue and can be dangerous.

Plastic: Empty container may retain product residues.

Other: No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION

Exposure Limits and Guidelines

This product does not contain any components with OSHA or ACGIH exposure limits.

Personal Protective Equipment

Eye/Face Protection: Eye protection is not required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety goggles.

Skin Protection: No skin protection is required for single, short duration exposures. For prolonged or repeated exposures, use impervious clothing (boots, gloves, aprons, etc.) over parts of the body subject to exposure. If handling hot material, use insulated protective clothing (boots, gloves, aprons, etc.). Launder soiled clothes. Properly dispose of contaminated leather articles including shoes, which cannot be decontaminated.

MATERIAL SAFETY DATA SHEET

MSDS Number: 13231

PENNZOIL® GEO PREMIUM ENGINE OIL - ALL GRADES

Page 4 of 8

Respiratory Protection: Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.

Personal Hygiene: Consumption of food and beverage should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, or smoking.

Engineering Controls / Work Practices

Ventilation: If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure or flammable limits.

Other: The OSHA permissible exposure limit (PEL) and ACGIH threshold limit value (TLV) for oil mist is 5 mg/m³. Chronic exposures below 5 mg/m³ are without significant health risks. The ACGIH short-term exposure limit (STEL) for oil mist is 10 mg/m³.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear , bright amber	
Odor: Petroleum	Vapor Pressure: No data available
Physical state: Liquid	Vapor Density (air=1): No data available
pH: No data available	Percent Volatile by Volume: No data available
Boiling Point: > 900 F, 482.2 C	Volatile Organic Content: No data available
Melting Point: Not applicable	Molecular Weight: No data available
Specific Gravity: < 1	Average Carbon Number: No data available
Pour Point: No data available	Viscosity @ 100 F: No data available
	Viscosity @ 40 C: No data available
Solubility in Water: Emulsifies in water	
Octanol / Water Coefficient: Log K_{ow} =	No data available

10. STABILITY AND REACTIVITY INFORMATION

Chemical Stability: Stable

Conditions to Avoid: High heat and open flames.

Incompatible Materials to Avoid: May react with strong oxidizing agents.

Other: No information available

11. TOXICOLOGICAL INFORMATION

Primary Eye Irritation: No information available

Primary Skin Irritation: No information available

Acute Dermal Toxicity: No information available

Subacute Dermal Toxicity: No information available

Dermal Sensitization: No information available

Inhalation Toxicity: No information available

MATERIAL SAFETY DATA SHEET

MSDS Number: 13231

PENNZOIL® GEO PREMIUM ENGINE OIL - ALL GRADES

Page 5 of 8

Inhalation Sensitization: No information available

Oral Toxicity: No information available

Mutagenicity: No information available

Carcinogenicity: The International Agency for Research on Cancer (IARC) has concluded that there is inadequate data to evaluate the carcinogenicity to experimental animals of this class of product. IARC has concluded there is sufficient evidence that used gasoline-engine motor oils produce skin tumors in experimental animals. Also, IARC has determined this class of products belongs to Group 3—"not classifiable as to its carcinogenicity to humans".

Reproductive and Developmental Toxicity: No information available

Teratogenicity: No information available

Immunotoxicity: No information available

Neurotoxicity: No information available

Other: No information available

12. ECOLOGICAL INFORMATION

Aquatic Toxicity: No information available

Terrestrial Toxicity: No information available

Chemical Fate and Transport: No information available

Other: No information available

13. DISPOSAL INFORMATION

Regulatory Information: All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded, may be a regulated waste. Refer to state and local regulations. Caution! If regulated solvents are used to clean up spilled material, the resulting waste mixture may be regulated. Department of Transportation (DOT) regulations may apply for transporting this material when spilled.

Waste Disposal Methods: Waste material may be landfilled or incinerated at an approved facility. Materials should be recycled if possible.

Other: No information available

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation (DOT)

Highway / Rail (Bulk): Not Regulated

Highway / Rail (Non-Bulk): Not Regulated

MATERIAL SAFETY DATA SHEET

MSDS Number: 13231

PENNZOIL® GEO PREMIUM ENGINE OIL - ALL GRADES

Page 6 of 8

For US shipments, US DOT law requires the shipper to determine the proper shipping description of the material that is being shipped. The shipping information and description contained in this section may not be suitable for all shipments of this material, but may help the shipper determine the proper shipping description for a particular shipment.

International Information

Vessel: IMDG Regulated: IMDG Not Regulated: X
Air: ICAO Regulated: ICAO Not Regulated: X

Other: No information available

15. Regulatory Information

Regulatory Lists Searched: The components listed in Section 2 of this MSDS were compared to substances that appear on the following regulatory lists. Each list is numerically identified. See Regulatory Search Results below.

Health & Safety: 10 - IARC carcinogen, 11 - NTP carcinogen, 12 - OSHA carcinogen, 15 - ACGIH TLV, 16 - OSHA PEL, 17 - NIOSH exposure limit, 20 - US DOT Appendix A, Hazardous substances, 22 - FDA 21 CFR Total food additives, 23 - NFPA 49 or 325

Environmental: 30 - CAA 1990 Hazardous air pollutants, 31 - CAA Ozone depleters, 33 - CAA HON rule, 34 - CAA Toxic substance for accidental release prevention, 35 - CAA Volatile organic compounds (VOC's) in SOCMI, 41 - CERCLA / SARA Section 302 extremely hazardous substances, 42 - CERCLA / SARA Section 313 emissions reporting, 43 - CWA Hazardous substances, 44 - CWA Priority pollutants, 45 - CWA Toxic pollutants, 46 - EPA Proposed test rule for hazardous air pollutants, 47 - RCRA Basis for listing - Appendix VII, 48 - RCRA waste, 49 - SDWA - (S)MCLs

International: 50 - Canada - WHMIS Classification of substance, 54 - Mexico - Drinking water - ecological criteria, 55 - Mexico - Wastewater discharges, 56 - US -TSCA Section (12)(b) - export notification

State Lists: 60 - CA - Proposition 65, 61 - FL - Substances, 62 - MI - Critical materials, 63 - MA - RTK, 64 - MA - Extraordinarily hazardous substances, 65 - MN - Hazardous substances, 66 - PA - RTK, 67 - NJ - RTK, 68 - NJ - Environmental hazardous substances, 69 - NJ - Special hazardous substances

Inventories: 80 - Canada - Domestic substances , 81 - European - EINECS, 82 - Japan - ENCS, 83 - Korea - Existing and evaluated chemical substances, 84 - US - TSCA , 85 - China Inventory

Regulatory Search Results:

No components appear on any of the regulatory lists searched.

U.S. TSCA Inventory: All components of this material are on the US TSCA Inventory.

SARA Section 313:

Chemical	CAS Number	Percent in Product
ZINC COMPOUNDS	MIXTURE	1.5

IARC: No information available

SARA 311 / 312 Categories

Acute: Chronic: Fire: Pressure: Reactive:
Not Regulated: X

Canadian WHMIS Classification

MATERIAL SAFETY DATA SHEET

MSDS Number: 13231

PENNZOIL® GEO PREMIUM ENGINE OIL - ALL GRADES

Page 7 of 8

Not a controlled substance under WHMIS

European Union Classification

Hazard Symbols:

No classification recommended

Risk Phrases:

No classification recommended

Safety Phrases:

No classification recommended

Other: No information available

16. OTHER INFORMATION

Health and Environmental Label Language

WARNING: Continuous contact with used gasoline engine oils has caused skin cancer in animal tests.

ATTENTION: Prolonged or repeated skin contact may cause oil acne or dermatitis. Repeated exposure to oil mist in excess of the OSHA limit (5mg/m³) can result in accumulation of oil droplets in pulmonary tissue.

Precautionary Measures: Avoid prolonged or repeated contact with eyes, skin and clothing. Avoid generation and inhalation of oil mists.

First Aid: Skin Contact: Wash skin with soap and water. Launder soiled clothes and discard oil-soaked shoes. If irritation persists seek medical attention. Eye Contact: Flush with water. If irritation persists seek medical attention. Ingestion: Do not induce vomiting. In general, no treatment is necessary unless large quantities of product are ingested. If discomfort persists seek medical assistance.

Instructions in Case of Fire or Spill: In case of fire, use water fog, foam, dry chemical or carbon dioxide. Water spray may be ineffective, but can be used to cool containers. Do not use a direct stream of water. Material will float and can be reignited on surface of water.

Spill or Leak: Dike and contain spill. Do not use water; soak up with absorbent material such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

Contains: highly refined petroleum distillate, mixture; zinc compounds, mixture; polymer additives, mixture.

KEEP OUT OF REACH OF CHILDREN. (If intended for retail also)

MSDS Revisions

Previous Version Date: 01/22/93

Previous Version Information

Revised all sections, new 16 section MSDS format.

Other

No information available

Prepared By:

SOPUS Products
P.O. Box 4427
Houston, TX 77210-4427 USA

MATERIAL SAFETY DATA SHEET

MSDS Number: 13231

PENNZOIL® GEO PREMIUM ENGINE OIL - ALL GRADES

Page 8 of 8

Disclaimer of Warranty: The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, SOPUS Products must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information, the results to be obtained from the use thereof, or that any such use do not infringe any patent. Since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.



Shell Canada Limited Material Safety Data Sheet

Effective Date: 2005-07-29
Supersedes: 2003-05-13

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: SHELL HYDRAULIC OIL 32
SYNOMYS: HYDRAULIC OIL
PRODUCT USE: Hydraulic Fluid

MANUFACTURER

Shell Canada Limited
 P.O. Box 100, Station M
 400-4th Ave. S.W.
 Calgary, AB Canada
 T2P 2H5

TELEPHONE NUMBERS

Shell Emergency Number	1-800-661-7378
CANUTEC 24 HOUR EMERGENCY NUMBER	613-996-6666
For general information:	1-800-661-1600
For MSDS information: (From 7:30 to 4:30 Mountain Time)	403-691-3982 403-691-2220

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

2. COMPOSITION / INFORMATION ON INGREDIENTS

THIS PRODUCT IS NOT A WHMIS CONTROLLED SUBSTANCE.
 See Section 8 for Occupational Exposure Guidelines.

3. HAZARDS IDENTIFICATION

Physical Description: Liquid Lightly Coloured Hydrocarbon Odour
Routes of Exposure: Exposure will most likely occur through skin or eye contact. Inhalation is only possible if the product is heated or mists are generated.

Hazards:

Inhalation of oil mist or vapours from hot oil may cause irritation of the upper respiratory tract.

For further information on health effects, see Section 11.

4. FIRST AID

Eyes: Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.

Skin: Wipe excess from skin. Wash contaminated skin with mild soap and water for 15 minutes. If material is injected under the skin, get medical attention promptly to prevent serious damage; do not wait for symptoms to develop.

Ingestion: Do not induce vomiting. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs. Not normally required; obtain medical attention if large amounts have been ingested.

Inhalation: Remove victim from further exposure. Additional first aid treatment is not ordinarily required.

Notes to Physician: In general, lubricating oils have low oral toxicity. High pressure injection under the skin may have serious consequences and may require urgent treatment.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry Chemical
Carbon Dioxide
Water Fog

Firefighting Instructions: Material will not burn unless preheated. Caution, spilled material is slippery. Do not use a direct stream of water as it may spread fire. Use water to cool fire exposed containers. Water may be used to flush spills away from exposure. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus.

Hazardous Combustion Products: Carbon monoxide, carbon dioxide and dense smoke are produced on combustion.

6. ACCIDENTAL RELEASE MEASURES

Eliminate all ignition sources. Isolate hazard area and restrict access. Wear appropriate breathing apparatus (if applicable) and protective clothing. Dike and contain land spills; contain water spills by booming. For large spills remove by mechanical means and place in containers. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations. Notify appropriate environmental agency(ies).

7. HANDLING AND STORAGE

Handling: Avoid excessive heat, formation of oil mist, breathing of vapours and mist of hot oil and prolonged or repeated contact with skin. Launder contaminated clothing prior to reuse. Properly dispose of contaminated leather articles, including shoes, that cannot be decontaminated. Use good personal hygiene.

Storage: Store in a cool, dry, well ventilated area, away from heat and ignition sources.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

The following information, while appropriate for this product, is general in nature. The selection of personal protective equipment will vary depending on the conditions of use.

OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):

Oil mist (mineral): 5 mg/m³ (STEL: 10 mg/m³)

Mechanical Ventilation: Not normally required. Make up air should always be supplied to balance air exhausted (either generally or locally). Local ventilation is recommended if oil mist is present or if exposure limit is exceeded.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: No special eye protection is routinely necessary. Wear safety glasses as appropriate.

Skin Protection: Not normally needed. Chemically-resistant gloves should be worn for frequent or prolonged contact with this product.

Respiratory Protection: Not normally required under intended conditions of use. If airborne concentration is high (e.g. when product is heated), use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges in combination with a P95 particulate filter.

9. PHYSICAL DATA

Physical State:	Liquid	Odour:	Hydrocarbon Odour
Appearance:	Lightly Coloured	Odour Threshold:	Not available
Pour Point, °C :	< -24 °C	Boiling Point, °C :	> 316 °C
Vapour Pressure (absolute):	< 0.1 mm Hg @ 20 °C	Vapour Density (air = 1):	Not available
Density:	869 kg/m ³ @ 15 °C	Flash Point, °C :	Cleveland Open Cup > 200 °C
Specific Gravity (Water = 1):		Lower Explosion Limit:	Not available
pH:	Not available	Upper Explosion Limit:	Not available
Viscosity:	28.8 - 35.2 cSt @ 40 °C	Autoignition Temperature, °C:	Not available
Evaporation Rate (n-BuAc = 1):	Not available	Partition Coefficient (K_{ow}):	Not available
Water Solubility:	Insoluble	Molecular Weight:	
Other Solvents:	Hydrocarbon Solvents	Formula:	

10. STABILITY AND REACTIVITY

Chemically Stable:	Yes	Hazardous Polymerization:	No
Sensitive to Mechanical Impact:	No	Sensitive to Static Discharge:	No
Incompatible Materials:	Avoid strong oxidizing agents.		
Conditions of Reactivity:	Avoid excessive heat, formation of vapours or mists.		

11. TOXICOLOGICAL INFORMATION

Routes of Exposure:	Exposure will most likely occur through skin or eye contact. Inhalation is only possible if the product is heated or mists are generated.
Formulation:	No data is specifically available for this product and therefore this toxicological information is based on data available for the ingredients.
Irritancy:	This product is not a primary skin irritant after exposure of short duration, is not a skin sensitizer and is not irritating to the eyes.
Chronic Effects:	Prolonged or repeated contact may cause various forms of dermatitis including folliculitis and oil acne. Long term intensive exposure to oil mist may cause benign lung fibrosis.

12. ECOLOGICAL INFORMATION

Environmental Effects:	Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities.
Biodegradability:	Not readily biodegradable.

13. DISPOSAL CONSIDERATIONS

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery (cement kilns, thermal power generation), 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority. Landfill absorbed material in a government approved site.

14. TRANSPORTATION INFORMATION**Canadian Road and Rail Shipping Classification:**

This product is not regulated under the Canadian Transportation of Dangerous Goods Regulations for transport by road and rail.

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations (CPR)* and the MSDS contains all the information required by the CPR.

DSL/NDSL Status:

THIS PRODUCT IS NOT A WHMIS CONTROLLED SUBSTANCE.

This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act. This product and/or all components are listed on the U.S. EPA TSCA Inventory.

Other Regulatory Status:

No Canadian federal standard; however, for general discharge guidance, federal installations limited to 15 mg/L for total oil and grease. Provincial criteria are likely and should be requested when notifying provincial authorities.

16. ADDITIONAL INFORMATION**Revisions:**

This MSDS has been reviewed and updated.

Changes have been made to:

Section 3

Section 4

Section 5

Section 8